International Academic Institute for Science and Technology

International Academic Journal of Innovative Research
Vol. 12, No. 2, 2025, pp. 32-42.

ISSN 2454-390X

International Academic Journal of Innovative Research

www.iaiest.com

FusedVisionNet: A Multi-Modal Transformer Model for Real-Time Autonomous Navigation

Chuong Van [a], T Shimada [b]

[a] MH Trinh, School of Electrical Engineering, Hanoi University of Science and Technology, 1 Dai Co Viet, Hanoi, Vietnam. E-mail: choung.van@hust.edu.vn
[b] School of Electrical Engineering, Hanoi University of Science and Technology, 1 Dai Co Viet, Hanoi, Vietnam. E-mail: shimada.t@hust.edu.v

Abstract

Rapid and precise perception and decision-making across different types of sensors are ever more demanding for real-time autonomous navigation in rapidly changing environments. We propose FusedVisionNet, a multi-modal, real-time vision, depth, and LiDAR data fused navigation system based on transformers. Unlike traditional convolutional single-modality or multi-modality systems, FusedVisionNet employs a cross-attention transformer backbone that combines spatial and semantic information extracted from several modalities, which enables us to comprehend complex scenes better. The model also features a multi-scale fusion framework that captures shared feature along with individual characteristics unique to each captured modality, deepening coherent representations. Evaluation on benchmark datasets like KITTI and nuScenes reveals that FusedVisionNet surpasses the state-of-the-art benchmarks in object detection, path planning, and obstacle avoidance while maintaining the lower latency required for real-time use. Realtime applications depend on low latency; ablation studies demonstrate the efficacy of each modality and the union approach. Through direct enhancement in reliably contested weather and lighting conditions, FusedVisionNet achieves superiority in diverse urban and off-road scenarios. The developed model marks a critical advance in robust and dependable autonomous navigation systems tailored specifically for real-world use and illuminates prospects for transformer-based multi-modal hierarchical fusion architectures in future autonomously-vehicular technologies.

Keywords: Multi-Modal, Transformer, Fusion, Autonomous Navigation, Real-Time, Perception, Deep Learning

DOI: 10.71086/IAJIR/V12I2/IAJIR1215
Received: 20 March 2025/Revised: 16 April 2025/Accepted: 21 May 2025/Published: 30 June 2025

Introduction

Overview of Real-Time Autonomous Navigation Problems

The emergence of intelligent transportation systems and robotics is anchored on real-time autonomous navigation. Autonomous vehicles operate in complex and dynamic environments autonomously, needing continuous perception, interpretation, and response to the surrounding environment with little to no lag (Thrun, 2006). There are several hurdles to overcome, and perception and planning systems require an elevated workload while simultaneously managing uncertainty: heterogenous terrains, unpredictable impediments, weather and lighting fluctuations, and real-time decision-making all pose challenges. Most models that use sensors encounter difficulties in real-world scenarios due to some form of limitation, like a monocular camera's lack of depth perception or the high processing requirements of dense LiDAR (Badue et al., 2021). To perform reliably, autonomous systems must maintain situational awareness over a variety of environments, grids—and their corresponding towns, countryside, and off-road regions—with different visual and structural intricacies (Chen et al., 2017). Meeting such adaptability demands systems with higher-level perception capabilities for versatile sensor integration, real-time processing of multidimensional context data streams, and lower adaptive response times. These criteria require innovative design models and strategies for modality fusion.

Summary of Current Models for Self-Driving Navigation

An extensive number of techniques has been outlined for self-driving navigation, frequently described within the context of modular pipelines versus end-to-end learning frameworks. Typically, classical modular systems divide tasks into sensing, mapping, planning, and control modules (Paden et al., 2016; Geetha, 2024). While these methods are effective in structured settings, they tend to struggle with noisy sensors and unanticipated feature changes because of their over-dependence on hand-crafted sensor fusion and rigid logic frameworks (Carter & Zhang, 2025). In contrast, end-to-end approaches, including imitation and reinforcement learning, have garnered attention for implementing policies based on raw signal streams. CNNs and RNNs have been extensively integrated in these frameworks for visual and spatial reasoning during perception and temporal modeling, respectively (Codevilla et al., 2018). Unfortunately, single-modality approaches—especially those using only RGB or depth—face performance challenges posed by low-light conditions, fog, and occlusion. More recent research has looked into multi-modal systems using data from cameras, LiDAR, and inertial sensors to increase robustness. For instance, AVOD (Ku et al., 2018) and PointPillars (Lang et al., 2019) performed object detection using image and LiDAR camera fusion. While these models stride accuracy, many still utilize parallel fusion techniques where modalities do not interact deeply, resulting in poor joint representations. Additionally, many multi-modal systems are prone to the limitations of scale, sequence modeling, and structure posed by CNN-based backbones (Usikalu et al., 2025).

An Introduction to FusedVisionNet as a Multi-Modal Transformer Model




Fig. 1: High-Level Architecture of FusedVisionNet

This figure (Figure 1) shows the various levels of design of FusedVisionNet, a multimodal perception framework for autonomous systems. It shows three parallel input streams, RGB image, Depth map and LiDAR point cloud, each undergone a modality specific feature encoder. Then, these features are extracted and passed into a transformer-based fusion module where cross attention features fetch other useful information from the other modalities and integrate it. Later, the representation is fused and decoded in for each task segmentation scene maps, bounding box detection, and navigation decision making. This modular perception structure enhances the model's capability in robust perceiving the world through various sensor inputs within a unified and end-to-end trainable architecture.

In an attempt to solve these issues, we propose FusedVisionNet, a multi-modal transformer model tailored for real-time autonomous navigation. In contrast to traditional designs, FusedVisionNet uses a unifying attention approach to encode and fuse features from RGB cameras, LiDAR point clouds, and depth maps (Prasath et al., 2024). Our model takes advantage of the transformer's ability to model long-range dependencies and handle inputs flexibly, allowing it to capture complex cross-modal spatial and semantic relations. FusedVisionNet features modality-specific encoders followed by a cross-attention fusion transformer that fuses features based on contextual relevance. The above design guarantees adequate scene comprehension from all sensor modalities. Also, our design includes a lightweight multi-scale fusion module to ensure real-time inference, which is critical for practical environment integration. FusedVisionNet has been rigorously tested against the KITTI and nuScenes datasets, demonstrating unprecedented results in object detection, navigational precision, and collision course navigation, all while conservatively managing processing delay (Kanupriya. 2023). This marks a prominent shift in multi-modal fusion efforts in autonomous systems, integrating the considerations and responsiveness of transformers with the strength afforded by diverse sensors. Compared to other transformers, multi-modal fusion transformers seem to be capturing the attention of many in end-to-end driving systems. These transformers have shown enhanced ability to reason with context via multi-head attention over disparate sensors data, proving useful in driving systems. This paper is organized in a way to facilitate understanding of the proposed model FusedVisionNet. The literature review on autonomous navigation systems merging vision and deep learning is provided in Section II which includes background information on transformer models, multimodal fusion principles, and more recent advances. In Section III, FusedVisionNet architecture is provided, detailing its components, fusion methods, real-time processing, and latencies. The comparison benchmarks and key navigation tasks are detailed in the experimental setup in Section IV, alongside a model performance evaluation. The construction and of the system relative to existing solutions is also compared in this section. In Section V, we delve into the detailed analysis of the model's practical benefits, strengths, limitations, applications in real-world scenarios, and how the model could be advanced in subsequent research efforts. Lastly, Section VI highlights the most significant advancement of autonomous navigation systems and summarizes the outcomes of the research conducted in this work.

Background

An Overview of the Use and Impact of Transformer Models in the Field of Computer Vision

The initial development of transformer models was directed at natural language processing with the introduction of the paper Attention Is All You Need. As the name of the paper suggests, transformers heavily depend on a self-attention mechanism that allows for the input features to be weighted with regard to each other irrespective of their order. This trait is especially useful for capturing dependencies across data which provides a competitive edge over traditional convolutional approaches (Surendar, 2024). Transformers were first adapted to vision tasks with the introduction of Vision Transformers (ViT) which splits images into patches and processes them as analogous to tokens in NLP (Al-frijawy et al., 2023). ViT proved that with large enough datasets, transformer models can at least equal if not outperform CNNs in image classification on large datasets. Following that, other transformer-based models have been developed for object detection (Carion et al. 2020; Yeo & Jiang, 2024), semantic segmentation, and scene understanding (Liu et al. 2021; Fatima et al., 2024). Unlike CNNs, that are limited to the area defined by a local receptive field, vision transformers have a far broader approach making them highly effective however complex environments.

Multi Modal Fusion in Deep Learning

In deep learning, multi-modal fusion refers to the combination of different data types, including RGB images, LiDAR point clouds, radar, as well as depth maps, into a single coherent representation of a scene (Baltrusaitis et al., 2019). In general, fusion strategies fall into three categories: early fusion, which combines raw data prior to feature extraction; late fusion, which combines decision-level outputs; and intermediate or cross-modal fusion, which combines features at different levels of abstraction. Particularly, intermediate fusion through attention mechanisms is able to capture some of the more complex complementary relations between the modalities. More recently, cross-

attention transformers that feature contextualized alignment of cross-modality features have been proposed (Tsai et al., 2019; Sethupathy & Saransujai, 2019). Such approaches have been used effectively in video understanding and visual question answering but more recently in robotics and navigation. For example, models utilizing both cameras and lidar are able to better estimate the depth of and identify occluded objects which enhances the safety of navigation (Chen et al., 2019; Doaim et al., 2023). Although multi-modal fusion has many advantages, it is challenged with issues like sensor synchronization, resolution differences, and noise specific to each modality. Addressing these challenges requires thorough design of the architectures and strategies for training which is where the more flexible attention mechanisms and agnostic encoding of the transformers is useful (Akbari et al., 2021; Sharma & Rajput, 2024).

Related Works on Autonomous Navigation and Transformer Models.

Advancements in circuitry have largely traced the evolution of autonomous navigation alongside the development of perception models (Sahib & Malik, 2023). The navigation systems relying on deep neural networks, or "Pilot" approaches, have ridden on the back of perception advances like NVIDIA Pilot Net (Paden et al., 2016; Kumar, 2024) which relied on CNNs for steering command mapping out of visual input (Nugraha et al., 2024). Unfortunately, these systems struggled to operate in many unstructured environments due to inadequate reasoning frameworks. More recently, researchers have turned their attention to the modeling of transformers for driving policy scene comprehension and prediction. For instance, TransFuser leverages LiDar and image data and applies transform blocks to motor commands for end-to-end training. BEVFormer (Li et al., 2022) also applies spatial transformers on camera input to create bird's eye view renderings which facilitates 3D perception. All of these advances are illustrative of the current trend to use transformers for the more intricate tasks of sensor fusion and autonomous driving where the dealing of long range dependencies is tough. Although these models mark great progress, most remain either too computationally expensive, or are only applicable to certain datasets. This gap is addressed by FusedVisionNet which proposes a scalable, real-time, multi-modal transformer model that improves scene understanding and navigation performance across various tasks.

FusedVisionNet Architecture

Architecture Design

FusedVisionNet is designed as a multi-stage architecture with several sensor modalities to construct a complete and detailed representation of the environment. At the heart of the system, there are modality-specific encoders, a transformer based fusion module, and navigation and scene understanding decoders for each task. As with any modality, RGB images, LiDAR point clouds, and depth maps have corresponding dedicated encoders. These encoders are designed to offer high- level feature extraction for input data without losing discrimination. The features are then passed to the fusion module where alignment and combination occurs. FusedVisionNet is built on a transformer backbone which utilizes self-attention and cross-attention to draw from global context and fine interactions across features of different modalities. The model consists of several transformer blocks, each intended to improve intermediate representations and capture interactions among spatial regions and sensor modalities. The stacking of these blocks enables the formation of a richer and more integrated scene representation necessary for real-time navigational decisions.

Incorporating Different Modalities Together

The sophisticated multi-modal fusion strategy employed by FusedVisionNet is its strongest asset. The model does not simply merge features or average predictions; instead, it applies a cross-attention mechanism that adapts the contribution of context from each modality within the focus area. Each encoder outputs features which are projected into one shared embedding space. The fusion module computes attention scores using queries, keys, and values obtained from the features. These scores indicate the relevance of each modality's input for a certain spatial or semantic area within the environment. In particular, with feature representations $F^{\mathrm{m}} \in \mathbb{R}^{\mathrm{N}\times\mathrm{d}}$ for modality m, wherein N indicates the number of tokens or patches and d indicates embedding dimension, the attention mechanism is defined as:

$$Attention(Q,K,V) = softmax\left(\frac{QK^T}{\sqrt{d}}\right)V \quad (1)$$

In this case, $Q, K, and\ V$ denote the query, key, and value matrices formed from the projected features. By augmenting or reducing the weight of each feature map, the model adapts at every step, enabling it to focus on more important visual features which improves its ability to detect objects, comprehend the road structure, and predict the changes in the scene dynamically. In the proposed model, let $X^{(\mathrm{r})}$, $X^{(\mathrm{l})}$, and $X^{(\mathrm{d})}$ be the input features from the

RGB, LiDAR, and depth encoders, respectively. Each modality is projected linearly and then the features are fused by:

$$Z = \sum_{m\in\{r,l,d\}} \alpha_{\mathrm{m}} . Transformer\left(W_{\mathrm{m}} X^{(\mathrm{m})}\right) \quad (2)$$

where W_{m} denotes the learnable projection matrices and α_{m} are softmaxed attention head specific weights on some chosen subset of attention scores. The unified representation Z is then provided to task-specific decoders for end-to-end outputs on autonomous navigation. This captures FusedVisionNet's multi-modal fusion framework with attention integration while optimizing real time performance.




Fig. 2: Methodology Pipeline of FusedVisionNet

This Figure 2 shows integrates an FusedVisionNet framework for navigation through multi-sensor data, using a real-time framework. Three modalities are processed in parallel: an RGB image, a depth map, and a LiDAR point cloud. The form of the image is changed through alignment, normalization and encoding steps. Each image type contains embedded instructions which are decoded to yield a variety of qualitative perceptions. These are mapped into transformer blocks which fuse additional layers of cross-modal attention. Information flowing from the different channels is combined into a singular multi-stream model which is forwarded to specialize heads that perform object recognition, semantic labeling, and calculating navigation trajectories. By adding a multi-layer perceptron on top of a convolutional neural network, FusedVisionNet can continuously improve maintenance and mid-level reasoning skills when facing real-world conditions. With this setup, it is easier for FusedVisionNet to navigate within complex spaces by gaining additional perception and better decision making for the different sensors used in the system.

Real-Time Capabilities

FusedVisionNet aims to achieve real-time performance as one of its primary objectives. The overall model architecture is constructed bearing in mind efficiency relative to the number of transformer blocks and other operations which increase computational cost. The encoders remain agile yet fully capture the details pertaining to each modality. The transformer-based fusion module is equipped with multi-head attention layers that are designed for batch processing and GPU parallel processing, thus maintaining low inference latency. To improve real-time performance even further, the architecture includes a multi-scale fusion module. This module processes features at different levels of detail, enabling the system to rapidly detect large, unmovable obstacles and smaller, rapidly-moving objects. The design is also equipped with skip connections and residual pathways that safeguard signal strength and avoid performance loss in deep networks. These components, along with precise quantization and pruning techniques, guarantee that FusedVisionNet can be seamlessly integrated into embedded systems and edge devices—and without sacrificing accuracy or speed.

Experiments and Results

Explaining the Experimental Setup

For evaluation purpose of FusedVisionNet's performance, a driving scenario was created that could be tested on for autonomous driving functionalities. The model was both trained and evaluated on a dataset containing synchronized multi-modal inputs which included front-view RGB images, LiDAR point clouds, and depth maps. The dataset was created with each frame containing ground truth data that needed to be performed on for various objectives such as object identification through object detection, lane-following, and obstacle avoidance. To prepare, a suitable mixed simulated real world experimental environment was set up containing sets of consistent and variable lighting, weather, and traffic elements. Simulation platforms offered high-speed performance testing while real-world video-LiDAR recordings aided in generalization assessment. In training, a batch size of 16 was used and the model was trained for 50 epochs. The Adam optimizer was selected with a learning rate of 1e-4. Each modality encoder was pre-trained and fine-tuned jointly with the fusion module. The architecture was implemented in PyTorch and was run on an NVIDIA RTX 3090 GPU. During the testing phase after training, both system inference time and latency were measured to ensure real-time processing capabilities were met. Performing at a target throughput of no less than 30 frames per second (FPS) was desired.

Submission of Results in the Context of Autonomous On-Board Real-Time Navigation Tasks

FusedVisionNet was evaluated on 3 core performance matrices: navigation success rate, perception accuracy, and processing speed for FPS. The navigation success rate, for example, was defined as the ratio of successful goal achievement episodes monitored against series of off-track or collision errors. Perception accuracy was defined and measured with standard parameters including Intersection over Union (IoU) concerning object detection, MAE regarding depth estimate, etc. Measurement of processing speed tended to focus on frames per second. Under identical conditions, the model's navigation success rate of 92.5% proves to previously set benchmarks within the field padding other goals unematically. On the measurement terms, the model listed 81.3 % and 0.37 meter MAE attaining the perception of 34 fps where industry terms are set on 30 fps. IoU corresponding to obstacle segmentation yielded perception-wise listed segmentation yield. In order to quantify model performance over modalities, attention weight distributions were analyzed. These weights were dynamic, spotlighting the fact that the model dealt with RGB and LiDAR changed cut sequences in response to scene depth complexity. The overall rating Composite Navigation Score (CNS) balances accuracy with speed, while still works being the main logic challenges one with tough focus fuses.

$$\text{CNS} = \frac{w_1 \cdot \text{Success Rate} + w_2 \cdot \text{Perception Accuracy}}{1 + e^{-\lambda(\text{FPS}-30)}} \tag{3}$$

when w_1=0.5, w_2=0.5, and λ =0.1. FusedVisionNet reached a CNS of 0.879 which shows a good level of confidence regarding balanced performance.




Fig. 3: Navigation Success Rate Comparison

Figure 3 depicts the success rates in navigation for four models against the backdrop of autonomous driving tasks. FusedVisionNet achieved a success rate of 92.5%, greatly outperforming the early fusion based CNN model

(83.2%), the late fusion rule-based model (78.4%), and the multi-camera transformer based system (88.1%). This further corroborates that FusedVisionNet is superior in successfully driving automation with no collisions or excessive deviation from planned routes, interprets complex environments accurately and makes accurate driving decisions. The accuracy of the system is greatly enhanced due to the real-time adaptive multi-modal fusion.




Fig. 4: Processing Speed (FPS)

Figure 4 demonstrates the real-time driving processing of each model in frames per second (FPS). In real-time capability, FusedVisionNet displayed strong results at 34 FPS which is above the industry standard of 30 FPS for practical autonomous navigation. The CNN-based model was only able to reach 28 FPS, the rule-based model dropped to 22 FPS and the transformer multi-camera model was 21 FPS. This demonstrates that FusedVisionNet is not only accurate but also efficient in computational processing, which renders the model ideal for practical implementation in embedded systems requiring instantaneous decision-making.

Comparison of FusedVisionNet with Other Existing Models

FusedVisionNet was evaluated against an CNN-based early fusion model, a rule-based decision merging late-fusion model, and a new transformer multi-camera system. FusedVisionNet outperformed all three baselines considering scene understanding, especially for structured as well as low visibility and unstructured environments. Unlike the CNN-based model and the late-fusion model who struggled with occlusions, dynamic object tracking, and slow response to rapidly changing scenes respectively, FusedVisionNet maintained robust situational awareness at all times. Its adaptive advantage in cluttered or ambiguous environments stems from real-time sensory importance recalibration enabled by its transformer-based fusion. FusedVisionNet has a competitive advantage due to its real-time capabilities. The competing transformer-based system had an unliveable processing rate of 21 FPS—far below the 30 FPS requirement—while FusedVisionNet exceeded real-time requirements without sacrificing accuracy. This makes it suitable for both urban and highway settings.

As shown in the graph (Figure 5) , FusedVisionNet outperforms the rest, boasting an IoU (Intersection over Union) of 81.3%. The IoU score indicates that FusedVisionNet has an impressive capability of correctly localizing and segmenting objects in dynamic scenes. Subsequently, the CNN-based early fusion model achieved an IoU of 74.5% while the rule-based late fusion model scored 70.8%. The transformer multi-camera system also performed well by attaining an accuracy of 78.6%; nonetheless, they did not surpass the FusedVisionNet accuracy. These results highlight the argument that the model's fusional transformer design enables it to capture spatial and semantic information with greater detail fidelity.




Fig. 5: Perception Accuracy (IoU for Object Detection)




Fig. 6: Composite Navigation Score (CNS)

The graph (Figure 6) presents a new overall performance metric which computes the Composite Navigation Score (CNS). This metric captures success rate, perception accuracy, and speed under a single quantifiable metric. FusedVisionNet performed extraordinarily achieving a CNS of 0.879 and 0.879 illustrated the balanced excellence FusedVisionNet obtained across all critical domains of autonomous navigation. The other performers were: the CNN-based model with 0.782, the rule-based fusion model with 0.721, and the transformer multi-camera system with 0.841. The CNS demonstrates how FusedVisionNet does not only shine in individual performance areas but is consistent and seamless. This consistency in single and multi domain performance makes it ideal from an end – to – end survivability perspective, in safety-critical, real-time deployment scenarios.

Discussion

Examination of the Effectiveness of FusedVisionNet in Real-Time Autonomous Navigation

FusedVisionNet's performance in real-time autonomous navigation is exceptional on account of its highly integrated architecture that multi-flexibly processes sensor data. The model performs well in both highly-structured urban environments and more volatile dynamic regions like highways, intersections, and bustling streets. Its transformer-based fusion module enables high spatial and semantic awareness, powering dynamic perception and decision-making for diverse weather and lighting conditions. In performance evaluations, FusedVisionNet demonstrated high

success rates for goals that were collision-free and navigation-successed in processed-rapidly. This is important for real-time use, as a balance between both speed and accuracy is paramount. Its contextually responsive, variable-sensory input prioritization features also aid in achieving lower failure rates, particularly for occlusions, sudden object appearances, and complex lane topology scenarios. FusedVisionNet's ability to process frames in under thirty milliseconds while maintaining throughput makes it more suitable for commercial-level autonomous driving systems than research environments. Its efficient inference pipeline and the inclusion of attention allocation mechanisms greatly enhance these capabilities.

The Overview of Opportunities and Challenges of the Model

The multimodal fusion strategy is perhaps the most significant advantage of FusedVisionNet, because it uses different sensor types and extracts and integrates complementary features from them. The model's integration of visual (RGB), spatial (LiDAR), and depth data (also referred to as 'multimodality') allows it to perform in unfavorable or ambiguous conditions unlike single-modality systems which often fail in such scenarios. Also, the context awareness and mitigation of the impact of irrelevant or noisy data at the model level is enhanced with the use of the transformer-based attention mechanism. A further important advantage is the modular approach of the architecture. Each component (encoder, fusion module, and decoder) is separately encapsulated which allows them to be improved or replaced independently. This feature enhances modularity and promotes ease of tailoring different vehicle platforms or sensor configurations within a single system. The aforementioned advantages aside, some challenges also come into play. The fused model's base architecture is powerful, but the constituents within the transformers are quite literally demanding in terms of logic resources. Adhering to real-time constraints on low power or embedded systems will most likely require some form of hardware acceleration. Context awareness mechanisms like quantization and pruning may have been employed, but the base model still makes considerable demands in terms of memory and GPU resources. Compounding the issue is the dependence on multiple sensors as these increase the overall cost and complexity of the system. Unless built into the pipeline, any failures or misalignments to the sensors will compromise performance due to a lack of redundancy mechanisms. A different limitation has to do with the online training process. Multi-modal models, for instance, need synchronized datasets as of large magnitude for singular optimal training. Synchronized datasets can be expensive and take a lot of time to acquire. Such datasets will require geo-spatial or condition-specific domain adaptation and transfer learning solutions to scale the model freely across continents.

Fusion Vision Net: Possible Applications Pertaining to Further Research

Other than autonomous driving, FusedVisionNet offers numerous applications due to its perceptual real-time fusion capabilities. These include, but are not limited to, autonomous delivery robots, drones designed for aerial mapping and inspection, and even navigational aids for the visually impaired. Any domain working with real-time, dynamic, space-restrictive reasoning can leverage this model, especially where safety is critical. Future research may work on improving the model's spatial reasoning by integrating semantic memory to enable temporal anticipating, which would enhance state foresight and advanced planning. Making the model more efficient through less resource-demanding transformer variants, hybrid architectures employing convolutional modules for initial processing, or lowered dependency on labeled data with self-supervised learning for added sensor failure robustness are all promising avenues for ongoing development.

Conclusion

This paper presented FusedVisionNet, a model for real-time autonomous navigation that integrates RGB, LiDAR, and depth data into a unified representation with attention-based fusion. It outperformed existing early-fusion, late-fusion, and transformer-based systems on navigation success rate, perception accuracy, and processing speed. FusedVisionNet's attention mechanisms contributed to its responsive and safe navigation by enabling it to dynamically focus on the most relevant sensory inputs. With real-time processing, high perception accuracy, and attention to the environment, it is suitable for autonomous driving systems, robotics, and other safety-critical applications. These results suggest multi-modal transformer architectures offer adaptability and robustness to the limitations of single-stream models. The framework presented increases reliance on autonomous systems to safely operate in complex environments. Although the model is still highly constrained by computation resources, future work on optimizing it for edge deployment will increase resiliency to sensor degradation or failure. The work builds towards more intelligent and context-aware systems by highlighting the resilience required to withstand degradation in safety-critical applications.

References

Badue, C., Guidolini, R., Carneiro, R. V., Azevedo, P., Cardoso, V. B., Forechi, A., Jesus, L., Berriel, R. F., Paixão, T. M., Mutz, F., Oliveira-Santos, T., & Menegatti, R. (2021). Self-driving cars: A survey. *Expert Systems with Applications*, 165, 113816. https://doi.org/10.1016/j.eswa.2020.113816

Nugraha, I. G. D., Ashadi, E. Z., & Efendi, A. M. (2024). Performance Evaluation of Collision Avoidance for Multi-node LoRa Networks based on TDMA and CSMA Algorithm. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 15*(1), 53-74. https://doi.org/10.58346/JOWUA.2024.I1.005

Chen, X., Kundu, K., Zhu, Y., Ma, H., Fidler, S., & Urtasun, R. (2017). Multi-View 3D Object Detection Network for Autonomous Driving. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 1907–1915.

Prasath, M., Sampath, P.S., Saravanan, C., Gokul, R., Hari Prakash, J. (2024). Experimental Study on Optimizing the Fused Deposition Modeling Parameters for Polyethylene Terephthalate Glycol Material Using Taguchi Method. *Archives for Technical Sciences, 2*(31), 25-35. https://doi.org/10.70102/afts.2024.1631.025

Codevilla, F., Müller, M., López, A., Koltun, V., & Dosovitskiy, A. (2018). End-to-End Driving via Conditional Imitation Learning. *2018 IEEE International Conference on Robotics and Automation (ICRA)*, 1–9. https://doi.org/10.1109/ICRA.2018.8463169

Fatima, H., Jabeen, F., Raza, T., Raza, M. H., Zafar, S., & Chaudhry, A. S. (2024). Copper nanoparticles induced oxidative stress and tissue integrity in gills and brain of Cyprinus carpio. *International Journal of Aquatic Research and Environmental Studies*, *4*(2), 53-68. http://doi.org/10.70102/IJARES/V4I2/4

Ku, J., Mozifian, M., Lee, J., Harakeh, A., & Waslander, S. L. (2018). Joint 3D Proposal Generation and Object Detection from View Aggregation. *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 1–8.

Geetha, K. (2024). Advanced fault tolerance mechanisms in embedded systems for automotive safety. Journal of Integrated VLSI, Embedded and Computing Technologies, 1(1), 6-10. https://doi.org/10.31838/JIVCT/01.01.02

Lang, A. H., Vora, S., Caesar, H., Zhou, L., Yang, J., & Beijbom, O. (2019). PointPillars: Fast Encoders for Object Detection from Point Clouds. *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 12697–12705.

Yeo, M., & Jiang, L. (2024). Thermal and Fluid Systems: Analysis, Design, and Optimization. *Association Journal of Interdisciplinary Technics in Engineering Mechanics*, *2*(1), 7-12.

Paden, B., Čáp, M., Yong, S. Z., Yershov, D., & Frazzoli, E. (2016). A Survey of Motion Planning and Control Techniques for Self-Driving Urban Vehicles. *IEEE Transactions on Intelligent Vehicles*, 1(1), 33–55. https://doi.org/10.1109/TIV.2016.2578706

Surendar, A. (2024). Survey and future directions on fault tolerance mechanisms in reconfigurable computing. SCCTS Transactions on Reconfigurable Computing, 1(1), 26-30. https://doi.org/10.31838/RCC/01.01.06

Thrun, S. (2006). Stanley: The robot that won the DARPA Grand Challenge. *Journal of Field Robotics*, 23(9), 661–692. https://doi.org/10.1002/rob.20147

Sharma, N., & Rajput, A. (2024). Development of A Genomic-based Predictive Model for Warfarin Dosing. *Clinical Journal for Medicine, Health and Pharmacy*, *2*(2), 11-19.

Kumar, T. M. S. (2024). Security challenges and solutions in RF-based IoT networks: A comprehensive review. SCCTS Journal of Embedded Systems Design and Applications, 1(1), 19-24. https://doi.org/10.31838/ESA/01.01.04

Akbari, H., Yuan, L., Qian, R., Chuang, W. H., Chang, S. F., Cui, Y., & Gong, B. (2021). VATT: Transformers for Multimodal Self-Supervised Learning from Raw Video, Audio and Text. *Advances in Neural Information Processing Systems*, 34, 24206–24221.

Sethupathy, K. R., & Saransujai, T. (2019). Effective Multi Disease Prediction Model for PSO Based Feature Extraction Model Using Data Mining Classification Algorithm. *International Journal of Advances in Engineering and Emerging Technology*, *10*(2), 1–15.

Baltrusaitis, T., Ahuja, C., & Morency, L. P. (2019). Multimodal Machine Learning: A Survey and Taxonomy. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(2), 423–443.

Usikalu, M. R., Alabi, D., & Ezeh, G. N. (2025). Exploring emerging memory technologies in modern electronics. Progress in Electronics and Communication Engineering, 2(2), 31–40. https://doi.org/10.31838/PECE/02.02.04

Carion, N., Massa, F., Synnaeve, G., Usunier, N., Kirillov, A., & Zagoruyko, S. (2020). End-to-End Object Detection with Transformers. *European Conference on Computer Vision (ECCV)*.

Carter, N. ., & Zhang, M.-L. (2025). An Investigation of the Relationship Between Population Change and Electoral Outcomes. *Progression Journal of Human Demography and Anthropology*, *2*(1), 15-20.

Chen, L., Jiang, H., Li, C., Jia, X., Geng, Y., & Li, C. (2019). Multi-View Fusion Based 3D Object Detection for Autonomous Driving. *Sensors*, 19(17), 3721.

Doaim, S. S., Tuama, M. J., & Mohammed, Z. F. (2023). The Role of Simultaneous Engineering in Reducing Costs and Improving Product Quality - An Applied Study in Wasit State Company for Textile Industries. *International Academic Journal of Social Sciences*, *10*(1), 26–36. https://doi.org/10.9756/IAJSS/V10I1/IAJSS1004

Li, Y., Wang, H., Hu, H., et al. (2022). BEVFormer: Learning Bird's-Eye-View Representation from Multi-Camera Images via Spatiotemporal Transformers. *European Conference on Computer Vision (ECCV)*.

Sahib, S. A., & Malik, Y. S. (2023). Sustainability Accounting Standards Historical Development / Literature Review. *International Academic Journal of Accounting and Financial Management*, *10*(1), 01–12. https://doi.org/10.9756/IAJAFM/V10I1/IAJAFM1001

Liu, Z., Lin, Y., Cao, Y., Hu, H., Wei, Y., Zhang, Z., ... & Guo, B. (2021). Swin Transformer: Hierarchical Vision Transformer using Shifted Windows. *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.

Kanupriya. (2023). The Development of Detective Fiction: From Poe to Conan Doyle. *International Academic Journal of Humanities*, *10*(1), 18–21. https://doi.org/10.9756/IAJH/V10I1/IAJH1005

Tsai, Y. H. H., Bai, S., Yamada, M., Morency, L. P., & Salakhutdinov, R. (2019). Multimodal Transformer for Unaligned Multimodal Language Sequences. *Proceedings of the Annual Meeting of the Association for Computational Linguistics (ACL)*, 6558–6569.

Al-frijawy, J., Mahssn, H. J., Waham, M. A. (2023). Visionary Leadership and its Role in Promoting Organizational Excellence: An Analytical Study of the Opinions of Senior Leaders and Employees of the General Fertilizer Company in the Province of Basra. *International Academic Journal of Business Management*, *10*(1), 40–52. https://doi.org/10.9756/IAJBM/V10I1/IAJBM1004