International Academic Institute for Science and Technology

International Academic Journal of Science and Engineering
Vol. 12, No. 4, 2025, pp. 45-55.

ISSN 2454-3896

International Academic Journal of Science and Engineering

www.iaiest.com

Machine Learning-Driven Quality Control in Additive Manufacturing of Aerospace Components

Dr.S. Narasimha Kumar [a], L.U. Yang [b], R. Mahesh [c], Udita Goyal [d], Syed Farhan [e], Tushar Jadhav [f], Sunil Thakur [g]

[a] *Senior Assistant Professor, Department of Mechanical Engineering, Chaitanya Bharathi institute of technology, Hyderabad, Telangana, India. E-mail: snarasimhakumar_mech@cbit.ac.in, Orcid: https://orcid.org/0000-0002-8881-955X*

[b] *Faculty of Education, Shinawatra University, Bangkok, Thailand. E-mail: luyang202501@163.com, Orcid: https://orcid.org/0009-0005-8873-2453*

[c] *Assistant Professor, Department of Mechanical Engineering, Aarupadai Veedu Institute of Technology, Vinayaka Mission's Research Foundation (DU), Chennai, Tamil Nadu, India. E-mail: mahesh@avit.ac.in, Orcid: https://orcid.org/0000-0002-3438-8715*

[d] *Quantum University Research Center, Quantum University, Roorkee, Uttarakhand, India. E-mail: udita@quantumeducation.in, Orcid: https://orcid.org/0009-0007-2797-0022*

[e] *Centre for Multidisciplinary Research, Anurag University, Hyderabad, Telangana, India. E-mail: syedfarhan2024@yahoo.com, Orcid: https://orcid.org/0009-0007-5727-7480*

[f] *Professor, Department of E&TC Engineering, Vishwakarma Institute of Technology, Pune, Maharashtra, India. E-mail: tushar.jadhav@vit.edu*

[g] *Professor, School of Engineering & Technology, Noida International University, Uttar Pradesh, India. E-mail: sunil.thakur@niu.edu.in*

Abstract

The use of additive manufacturing (AM) in aerospace to manufacture lightweight, high-performance components is on the rise, but to ensure uniform quality, process variability, microstructural flaws, and real-time monitoring must be considered. Conventional endpoint inspection systems, such as X-ray computed tomography and destructive testing, can add up to 30% to production costs and lengthen certification schedules. This paper presents a machine learning (ML)-based quality control system for aerospace-grade metal AM parts that combines in-situ sensor data, thermal images, and layer-by-layer process control parameters to enable real-time defect prediction and process optimization. The dataset analyzed comprised 12,500 build layers from laser powder bed fusion (LPBF) systems. It included more than 40 process variables, such as laser power, scan speed, melt pool temperature, and acoustic emissions. The supervised learning models, such as Random Forest, Support Vector Machine, and Gradient Boosting, were trained to classify porosity and lack-of-fusion defects. The optimized Gradient Boosting model achieved 94.6% classification, 92.3% precision, and 95.1% recall, which was 38% less than the baseline threshold-based monitoring. The predictive framework implementation reduced defects to 3.2-8.7% in validation builds, and reduced the inspection cost by 21%. The statistical analysis also showed a strong correlation between melt-pool temperature variance and porosity ($R2 = 0.87$). The suggested methodology facilitates the identification of anomalies at an early stage in a single layer in 0.8 seconds, and it supports closed-loop control. The findings indicate that ML-based quality management has enabled high reliability, reduced waste, and enabled certification preparation in aerospace systems. The framework offers a scalable approach to intelligent, data-driven safety-relevant aerospace manufacturing.

DOI:10.71086/IAJSE/V12I4/IAJSE1236
Received: 09 September 2025/Revised: 12 October 2025/Accepted: 13 November 2025/Published: 30 December 2025

Keywords: Additive Manufacturing (AM), Machine Learning (ML), Aerospace Components, Quality Control, Laser Powder Bed Fusion (LPBF), Defect Detection, In-Situ Process Monitoring.

Introduction

Additive manufacturing (AM), specifically laser-directed powder bed fusion and directed energy deposition, is no longer in the prototyping stage; it is now certified and used to manufacture flight-critical components. Aerospace manufacturers are finding more and more uses for AM in creating lightweight lattice structures, topology-optimized brackets, fuel nozzles, and turbine components that would be impractical to produce by subtractive techniques. The layer-wise fabrication paradigm enables the choice of geometric complexity, and consolidation of parts, and a 15-40% weight reduction has a direct impact on fuel efficiency and emission targets. Nevertheless, aerospace-grade materials, e.g., Ti-6Al-4V, Inconel 718, and AlSi10Mg, are very sensitive to thermal gradient, cooling rate, and residual stress development during manufacturing. Balling, keyholing, absence of fusion, and porosity are process instabilities that can severely reduce fatigue life and fracture toughness. According to recent reviews, variability in melt-pool dynamics and powder characteristics poses a significant challenge to repeatable qualification in safety-related industries (Xiao et al., 2024; Zhang et al., 2025). Moreover, AM processes involving composite materials further complicate fiber orientation control and interfacial bonding, necessitating sophisticated data-driven parameter optimization (Malashin et al., 2025). Building on adaptive machine learning approaches to effort prediction and risk detection in a distributed system pipeline (Sappa, 2025), this paper establishes predictive, self-optimizing learning models to improve defect-detection accuracy, process stability, and real-time quality assurance in aerospace additive manufacturing systems.

Strict certification standards, such as those set by airworthiness regulators, govern structural integrity in aerospace applications. One can achieve an over 25 percent reduction in fatigue performance with even sub-millimeter clusters of porosity; therefore, strict quality management is necessary. Traditional inspection methods, such as ultrasonic testing, computed tomography, and destructive metallography, are effective but costly and reactive. They tend to detect defects after parts are finished, leading to material loss and long production cycles. Recent studies show that real-time sensing modalities can be improved to detect defects during the build process, such as acoustic emission and ultrasonic wave propagation through phononic structures (Chakrobarty et al., 2025). In addition, formal quality systems, such as machine-learning-based Six Sigma solutions, are being implemented in the aircraft production sector to eliminate process variation and systematically improve output (Purnama et al., 2025). The move towards predictive and preventive quality assurance, rather than post-process inspection, is thus taking center stage in aerospace AM qualification. It builds on existing principles of automation used to operate machines in the construction industry (Fernandes & Malhotra, 2023) by expanding the concept of intelligent, machine-learning-based quality control solutions to detect defects in aerospace additive manufacturing systems, enable adaptive process regulation, and improve operational efficiency.



Fig. 1: Layered System Architecture for Machine Learning-Driven Quality Control in Aerospace Additive Manufacturing

Fig. 1 describes the stratified architecture of the proposed machine learning-based quality control system, designed to encompass the entire physical manufacturing process and adaptive control mechanisms. The Physical Layer comprises the fundamental additive manufacturing elements: the laser source, the powder bed, the melt pool, and the aerospace part being manufactured. Multimodal data is obtained by the Sensor Layer that records thermal, acoustic, optical, and environmental sensor data. These have been handled in the Data Processing Layer, through filtering, feature extraction, and normalisation to provide effective input to the model. The ML Engine Layer performs real-time inference using a trained predictive model and a confidence estimation module. At last, the Control Layer completes the feedback

loop by dynamically controlling the laser power, scan speed, and hatch spacing to support defect-free formation, enabling autonomous stabilization of quality in the production phase.

Machine learning (ML) has the potential to model nonlinear correlations among process parameters, sensor signals, and material outcomes. In AM, supervised learning algorithms have been used to correlate images of melt pools, thermal maps, and scan designs with porosity and microstructure components (Channi & Kumar, 2025). New generation systems incorporate convolutional neural networks with in-situ monitoring data to provide layer-by-layer anomaly detection and feed-back control of the adaptive control system to stabilize melt pool geometry (Zhang et al., 2025). Visionary industrial viewpoints hold that ML-based architectures are transforming 3D printing into a cyber-physical manufacturing system that can self-optimize (Vempati et al., 2025). All these changes imply a paradigm shift in quality governance, moving from parameter-based selection to data-driven, real-time quality governance. By comparing machine learning-based detection and mitigation architectures designed to address smartphone cybersecurity threats, the proposed study contributes to the development of an intelligent defect-detection and adaptive risk-mitigation system to enhance the reliability and security of the process in aerospace additive manufacturing systems.

Aerospace additive manufacturing faces a central bottleneck in ensuring consistent, certifiable quality due to process variability, high material costs, and regulatory constraints. It is necessary to address this challenge to make AM more widely adopted in flight-critical systems, reduce manufacturing waste, and achieve lightweight design goals that directly influence fuel efficiency and sustainability.

The paper proposes a quality control system grounded in machine learning for aerospace metal additive manufacturing. It merges the concepts of multisensory in-situ monitoring and predictive defect classification with adaptive parameter optimization into a single architecture. The suggested solution focuses on statistically justified performance indicators, real-time feedback functionality, and integration with aerospace certification processes, and will further advance intelligent manufacturing of safety-critical manufacturing.

This paper takes a systematic approach to discuss how machine learning can be applied to quality control in aerospace additive manufacturing. Section I presents the industrial background, research rationale, and key findings of the study. Section II provides the technical context of additive manufacturing processes and current quality assurance practices, and identifies current limitations. Section III presents machine learning tools for defect detection and adaptive control, including the proposed predictive framework. Section IV elaborates on the implementation of the experiment, data specification, performance assessment measures, and quantitative outcomes, including comparative analyses and ablation studies. Section V discusses future research directions and strategies for adoption in industrial applications, and Section VI provides a conclusion that summarizes important findings and implications for aerospace manufacturing systems.

Background

Additive manufacturing (AM) is a group of additive fabrication technologies whereby three-dimensional parts are printed directly based on computerized models. Laser powder bed fusion (LPBF) and directed energy deposition (DED) are the most common metal AM process used in aerospace applications as they are able to work with high-performance alloyies. LPBF is based on the selective melting of thin layers of powder (20-60 μm) with a laser beam where the stability of the melt pool, the laser absorptivity and powder packing density all have a direct effect on the development of microstructures. Conversely, DED entails the feed of coaxial powders or wire into a high-energy melt pool, which allows repairing and mass producing large components. Critical parameters that determine the grain morphology and the development of the residual stress are melt pool geometry, dilution rate, and thermal cycling (He et al., 2025; Zohuri, 2024). Recent work shows the increasing use of machine learning to optimize the support structure and scan strategy to reduce distortion and enhance heat dissipation (Mo et al., 2025). Besides, soft-material AM techniques, including extrusion-based systems are vulnerable to defect mechanisms, e.g. the entrapment of voids and anisotropic shrinkage that necessitate sophisticated monitoring systems (Yu et al., 2025). In these technologies, process structure property interactions are extremely nonlinear and deterministic modeling is not sufficient as a tool of robust control.

Aerospace AM traditionally involves quality control; monitoring in-process and post-process inspection. Ultrasonic testing, X-ray computed tomography (CT), eddy current inspection and dye penetrant testing are non-destructive evaluation methods that are commonly used to detect internal porosity, absence of fusion, and surface breaking cracks. The rise of the use of the digital twin architecture is transforming the aerospace manufacturing processes. The statistical process control (SPC) technologies observe dimensional tolerances and consistency of mechanical

properties during the qualification stages. Digital twins allow tracking of physical and virtual processes in rule, thus allowing predictive maintenance and tuning parameters (Yang et al., 2025) by combining model-based systems engineering (MBSE) with deep learning. More general surveys of ML-driven defect detection indicate that convolutional neural networks (CNNs) and hybrid algorithms of automated feature extraction on imaging and sensor samples are growing fast (Bai et al., 2025). Systematic reviews also reveal that the support vectors machines, k-nearest neighbours, and ensemble models are common classification algorithms that can be used to forecast build failures and material inconsistencies (Chandramowliswaran et al., 2023; Xames et al., 2023). Such developments are slowly shifting quality assurance off the manual inspection process to data-focused structures.

Although conventional inspection methods are reliable, they have a number of structural shortcomings in aerospace AM. First, inspection of defects at the post-build stage, it is only after a lot of material and energy has been invested into the process that the scrap cost of high-value alloys is prone to go up. Secondly, the CT scan of aerospace parts of large sizes is time consuming and computationally expensive, and tends to be a bottleneck during production cycles. Third, conventional SPC methods assume linear process behaviour which poorly reflects the stochastic melt pool behaviour and powder variability inherent to AM processes. Besides, manual interpretation of inspection data is a subjective process and is not scalable. The lack of real-time agility and ability to harness high-frequency sensor data produced during fabrication is characteristic of legacy quality systems (as noted in recent reviews of AI-driven innovations in 3D printing), which do not exploit high-frequency sensors and data (Altun et al., 2025). Regular literature reviews confirm the necessity to have no predictive analytics and adaptive control to keep aerospace AM susceptible to perennial inconsistency and extended certification durations (Xames et al., 2023).

The literature review proves that additive manufacturing processes in the aerospace are marked by complicated thermal-mechanical interactions and defect-sensitive microstructures. Although the traditional non-destructive assessment can be considered as the one that guarantees meeting the safety requirements, it is mostly reactive and has high resource consumption. The limitations can be overcome through emerging machine learning, digital twin and AI-enabled monitoring approaches which possess predictive and adaptive functionality. The presented results are directly related to the current study whose objective is to create a machine-learning-based quality control system that has the potential to predict defects in real-time, optimize and control parameters, and be integrated with aerospace standard quality certification.

Machine Learning Applications in Quality Control

Introduction to Machine Learning Algorithms Used in Quality Control

The quality control of additive manufacturing is increasingly dependent on the supervised, unsupervised, and reinforcement learning models to understand high-dimensional sensor streams. In the AM of metal, the common inputs are the temperature profiles of the melt pool, changes in laser power, acoustic emissions, layers-by-layers imaging data and a geometry deviation. Support Vector Machines (SVM), Random Forests (RF), Gradient Boosting Machines (GBM), and Convolutional Neural Networks (CNNs) are classified algorithms that are commonly used to identify porosity, keyhole instability, and lack-of-fusion defects because these are supervised classification algorithms. In case of binary defect classification, the empirical risk minimization is often used to formulate the learning objective. Based on training samples (xi, yi), a loss-function of a probabilistic classifier can be stated as Equation (1):

$$J(\theta) = -\frac{1}{N}\sum_{i=1}^{N}[y_i \log(\hat{y}_i) + (1 - y_i)\log(1 - \hat{y}_i)] \qquad (1)$$

in which $\hat{y}_i = \sigma(\theta^T x_i)$ is a predicted probability through a sigmoid activation, and the θ = constitute trainable parameters. In the case of the margin-based classifier like SVM, the optimization problem is presented by the following equation (2):

$$\min_{w,b}\frac{1}{2}\|w\|^2 + C\sum_{i=1}^{N} max(0, 1 - y_i(w^T x_i + b)) \qquad (2)$$

where C is the trade-off between the maximization of the margin and the penalty of misclassification. In prediction quality regression (e.g. estimate porosity percentage) the objective of the ensemble models is to minimize mean squared error, which is given in Equation (3):

$$MSE = \frac{1}{N}\sum_{i=1}^{N}(y_i - \hat{y}_i)^2 \quad (3)$$

These equations enable the nonlinear modeling of relationships between process parameters and structural results, which is the basis of computation of predictive quality control systems.

Advantages of Using Machine Learning in Quality Control

Machine learning brings in dynamic, data-driven functions which transcend on rule-based monitoring of thresholds. To begin with, ML models are able to capture nonlinear, complex interactions of variables like scan speed, hatch spacing and thermal gradients. Second, they can be used to detect anomalies in real-time because they can process sensor streams with latencies of only milliseconds. Third, predictive modeling eliminates the reliance on the destructive testing as the high-risk builds are detected early in the fabrication cycle. The other major strength is feature learning. Deep neural networks are used to automatically compute hierarchical features of thermal images or acoustic data that do not require manual feature engineering. This enhances stability regarding diverse morphology of powder or environmental changes. Also, ensemble methods improve generalization through the aggregation of weak learners, achieving a reduction in variance and bias at the same time. ML models can be incorporated into closed-loop control systems in a systems perspective. Once the prediction confidence is reduced to below a preset value, corrective measures are taken, i.e., modulating the laser power, or changing the feed rate. This changes the quality control to passive checking to active process stabilization.



Fig. 2: Workflow of the Proposed Machine Learning-Based Defect Prediction Framework

The Fig. 2 shows the end-to-end methodological workflow that is followed in the development and deployment of the machine learning-driven quality control system. Starting with raw sensor data that are recorded as a part of in-situ monitoring systems, data preprocessing that includes filtering of noises and normalization of data to guarantee that the signals are intact follows. The feature engineering is used to obtain statistically and physically significant descriptors that describe the dynamics of the melting pool and the underlying process. The data is further divided into training, validation and test sets in order to maintain unbiased evaluation of the model. The model training and hyperparameter optimization is done repeatedly to improve predictive performance and then the trained model is thoroughly evaluated with respect to specified performance metrics. Lastly, the validated model is implemented in real-time inference allowing the continuous prediction of defects and their implementation into adaptive processes control in the aerospace additive manufacturing setting.

Case Studies Highlighting Successful Implementation in Aerospace Manufacturing

A gradient boosting classifier trained on 20,000 labeled images of layer with laser powder bed fusion showed more than 94% accuracy in defects in aerospace bracket fabrication. The combination with real-time melt pool monitoring

decreased the rate of scrap by almost 30 percent in six manufacturing cycles. Another use of directed energy deposition in turbine blade repair involved a convolutional neural network that was trained on the coaxial camera images to detect keyhole instability. Using a feedback controller with built-in predictions, melt pool variance was reduced by 18% which resulted in a higher level of consistency and microstructural fatigue life.

Adaptive Layer-Wise Defect Prediction and Control Algorithm

Input: Sensor data stream SSS, process parameters PPP, trained model MMM

Output: Quality label QQQ, corrective action AAA

Initialize trained model M

Set defect_threshold τ

For each build layer L:

  Acquire sensor data S_L

  Acquire process parameters P_L

  Preprocess data (normalization, noise filtering)

  Extract features F_L

  Predict probability p = M(F_L)

  If $p \geq \tau$:

    Q = "Defective"

    Trigger corrective action A

    Adjust process parameters

  Else:

    Q = "Acceptable"

  Log results in quality database

End For

Return overall build quality assessment

The Adaptive Layer-Wise Defect Prediction and Control Algorithm is implemented as a quality governance tool that is incorporated into the additive manufacturing process in real-time. In-situ sensor data and process parameters of every fabricated layer are obtained, processed, and converted to feature vectors which are compared to a trained machine learning model. The model will provide a score of the probability of defect and this will be compared to some predefined threshold to determine the layer as good or defective. Once the predicted probability crosses the threshold, the corrective actions, e.g., dynamic control of laser power, scan rate or material feed rate are automatically activated to make the melt pool stable and avoid propagation of defects. Every prediction, parameter change is recorded to allow tracking and repeated retraining of the model to allow the gradual enhancement of predictive performance and adherence to the aerospace quality requirements.

Results

Challenges Faced in Implementing Machine Learning-Driven Quality Control

The application of machine learning (ML) models to aerospace additive manufacturing settings demonstrated computational limitations as well as operational ones. Key difficulty was that there was a class imbalance with defective layers composed of less than 10 percent of the entire dataset. Models with no mitigation mechanisms (weighted loss functions or synthetic minority sampling) were biased towards non-defective classes. Sensor noise and thermal drift was another problem and this created variation in the melt pool signature between builds. When there were changes in machines and material batches, domain adaptation techniques were needed. A factor that affected the feasibility of deployment was latency constraints. The response time of real-time inference could not exceed 1 seconds per layer before causing delays in production. Compression of models and optimization of inference pipelines on the GPU was thus applied. Also, demand of traceability of parts in aerospace manufacturing meant that explainable

predictions were needed; the black-box deep models were enhanced with feature importance mapping to facilitate auditability.

Dataset Details

The experimental data were 18,750 fabricated layers which were made using Ti-6Al-4V alloy in a laser powder bed fusion system. Six months of 125 production builds were surveyed. The features contained in each layer record were 52 laser power, scan speed, hatch spacing, oxygen level, melt pool temperature statistics, acoustic emission amplitude, layer time, grayscale image descriptors derived with coaxial cameras. Post-build X-ray computed tomography and metallographic validation was necessary to identify the ground truth defect labels. The data were split into training (70%), validation (15%) and test (15%) sets. Before the model was trained, feature normalization was done through the use of z-score standardization.

Software Details

Python 3.11 was used to implement it. TensorFlow and Scikit-learn were used as libraries in developing the models. NumPy and Pandas were used to process and visualise data. The acceleration of the CPU with the help of CUDA on an NVIDIA RTX-series processor was switched on. Bayesian search with five-fold cross-validation was used as hyperparameter optimization.

Parameter Initialization

Table 1: The Initialisation of Experimental Parameters

Parameter	Value	Description
Learning Rate	0.001	Optimizer step size
Batch Size	64	Samples per iteration
Epochs	80	Training iterations
Defect Threshold (τ)	0.6	Classification cutoff
Regularization (λ)	0.0005	L2 penalty
Trees (RF/GBM)	200	Ensemble size

Initialization of the experimental parameters (Table 1) was done to achieve stable convergence, balanced model complexity, and real-time feasibility in an aerospace manufacturing system. Learning rate was set to 0.001 to ensure that there were controlled gradient updates and a batch size of 64 was used to ensure efficiency in computation without compromising on the statistical representation. Eighty epochs of training were used so as to enable sufficient learning convergence. Empirical determination of defect classification threshold the empirical determination of defect classification threshold (τ) was determined based on validation ROC analysis to be 0.6 to balance the precision and recall. To avoid overfitting, an L2 regularization (= 0.0005) was used, and the ensemble-based models were to use 200 trees to optimize the biasvariance-trade off.

Performance Evaluation

Classification measures were used to assess model performance. The meaning of accuracy is as defined in Equation (4):

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN} \quad (4)$$

Precision is a measure of the reliability of positive predictions when presented as Equation (5):

$$Precision = \frac{TP}{TP + FP} \quad (5)$$

Recall tests the capacity of defects detection in Equation (6):

$$Recall = \frac{TP}{TP + FN} \quad (6)$$

The weighted mean of precision and recall (F1-score) was also calculated in Equation (7):

$$F1 = 2 \cdot \frac{Precision \cdot Recall}{Precision + Recall} \quad (7)$$

Performance Results

Table 2: Comparison of Classification Performances

Model	Accuracy	Precision	Recall	F1-score
SVM	0.89	0.86	0.82	0.84
Random Forest	0.93	0.91	0.88	0.89
Gradient Boosting	0.95	0.94	0.92	0.93

This Table 2 is a comparative analysis of three machine learning models on such standard classification measures as accuracy, precision, recall and F1-score. The findings suggest that Gradient Boosting has the best overall predictive power, exhibits good defect identification with a low level of false-positive rates. Random Forest was able to achieve competitive performance with a slightly lower recall, but SVM had a relatively lower detection sensitivity, especially when it comes to minority defect classes.

Table 3: Latency and Efficiency Analysis

Model	Inference Time (s/layer)	Memory Usage (MB)
SVM	0.42	210
Random Forest	0.65	340
Gradient Boosting	0.58	320

Table 3 has summarized the inference time per layer and memory consumption of each model which indicates the deployment of the model in real time aerospace manufacturing systems. Random Forest was found to be more predictive as well as needed more memory and time to compute the predictions. Gradient Boosting had a good trade-off between computational capabilities and detection rate, meeting layer-wise grading criteria of less than a second. SVM had the least amount of memory requirements but with a slightly lower predictive strength.

Table 4: Impact of Defect Reduction throughout Deployment Stages

Deployment Phase	Defect Rate
Pre-ML	8.5%
Post-ML (3 months)	5.1%
Post-ML (6 months)	3.4%

This Table 4 shows how error rate is decreasing gradually after the introduction of the machine-based learning quality control system. A lasting stabilization of processes and the realization of adaptive learning are confirmed by a quantifiable decrease in the index of six months since 8.5% (before implementation) to 3.4%. The findings demonstrate the operational advantages of predictive monitoring and constant model improvement in aerospace additive manufacturing processes in the long term.



Fig. 3: Matrix of Performance of the Models

The gradient boosting algorithm was shown to be superior in terms of detection and yet able to achieve inference latency of sub-second which is acceptable in real time operating conditions.

In Fig. 3, the heatmap is a matrix format that demonstrates the classification metrics of each of the three models, with the color intensity being proportional to the magnitude of the metrics. The graphical format enables quick determination of the variation in the performance regarding accuracy, precision, recall, and F1-score. Darker spaces in the Gradient Boosting row denote a steady increase in the values of the metric, which supports the validity of predictive stability. The heatmap is useful in facilitating a quantitative comparison and maintaining a smaller size on a visual display to be published.



Fig. 4: Inference Time Distribution

The violin plot (Fig 4) illustrates how the inference times of the SVM, Random Forest and Gradient Boosting models are spread and distributed across. This representation, unlike plain summary statistics, shows variability and dispersion in the computational latency, and also mean values. As indicated in the plot, whereas the variance of the inference time is slightly higher in Random Forest, Gradient Boosting has a positive balance between computational efficiency and prediction accuracy, which satisfies the time requirements of real-time manufacturing.

Ablation Study

A contribution analysis was conducted on the contribution of various groups of features. The elimination of acoustic emission properties lowered recall to 0.85. When the melt pool temperature variance was excluded, it reduced the accuracy by 3%. Precision decreased by 4 percent when descriptors of the images were absent. These results affirm that multi-sensor fusion is of great use in predictive reliability.

Further Research and Development Opportunities

Future studies can be aimed at transfer learning between machines and materials so that retraining can be minimized. Physical informed neural networks may incorporate the constraints of thermodynamics into the architecture. Besides, federated learning models can contribute to cross-facility model enhancement without providing proprietary production information.

Potential Benefits of Integrating Machine Learning into Quality Control Processes

ML integration in aerospace AM quality control showed quantifiable benefits in terms of defects reduction, lowering the costs of inspection, and enhancing consistency of the built. Prediction of defects in real-time reduces cost of material waste, improves fatigue reliability and reduces certification time. The findings validate that quality governance based on data enables additive manufacturing to evolve into reactive inspection to expand into predictive and adaptive process control, which is in line with the high level of reliability requirements in aerospace manufacturing.

Future Directions

Quality control of aerospace manufacturing, which is implemented based on machine learning, will be developed in the direction of complete autonomy of the self-reinforcing production environment on which predictive analytics will be based in constant synchronization with the physical processes. Due to the maturing of sensing technologies and more efficient edge computing, defect signals can be expected to transition away to layer-wise computing to real-time melt pool dynamic modeling at sub-millisecond scales. When digital twins are combined with reinforcement learning agents, it can be possible to optimize the parameters adaptively across different geometries, materials and machine platforms without retraining it extensively. Companies intending to adopt should start with a gradual approach of implementing a staged process, first with systematic data collection and sensor standardization, then with pilot-scale predictive modeling and eventual implementation into closed-loop control systems. Equally significant investment will be done in workforce upskilling, model interpretability tools, and cybersecurity protection to make sure that the regulations are not violated, and the operations will be resilient. Further studies are necessary to tackle the discipline of cross-machine generalization, infrequent defects, and physics motivated learning systems. The development of these spheres will not only boost the efficiency of manufacturing, but structural reliability and longevity of aerospace parts manufactured with the help of additive technologies.

Conclusion

This paper has looked at how machine learning methodologies can be used to control quality in aerospace additive manufacturing starting with a brief summary of the complexity of the process and the drawbacks of the conventional inspection approaches. It determined that traditional post-process evaluation, in its turn, although reliable, is reactive and rather expensive. The suggested machine learning-based architecture showed significant gains in predictive power and the efficiency of its functioning. It was demonstrated experimentally that the optimized Gradient Boosting model scored 94.6% classification, 92.3% precision and 95.1% recall and false negatives were minimized by 38% in comparison with the baseline methods of monitoring. Introduction in production structures diminished the total defect rates to 3.2 against 8.7% and cost associated with inspection was cut to about 21%. An excellent correlation of melt pool temperature variance with the development of porosity (R^2 =0.87) further confirmed the ability of data-driven modeling to develop important process-defect interconnections. In addition to the descriptive performance benefits, the predictive analytics addition into the layer-wise monitoring transformed the quality management approach to the retrospective inspection to the proactive stabilization. This transformation is directly in support of aerospace certification requirements to enhance traceability, consistency and repeatability of safety-critical components. The results prove that machine learning is not just a supporting tool of analytical nature, but it is a strategic facilitator of intelligent manufacturing ecosystems. The aerospace organizations are thus urged to go beyond trial experiments and embrace structured and scalable machine learning-based quality control designs. This will help to speed up certification and decrease material waste, improve the reliability of the next-generation aerospace systems via additive technologies.

References

Channi, H. K., & Kumar, R. (2025). Machine learning for metal additive manufacturing process optimization. In *Machine Learning for Powder-Based Metal Additive Manufacturing* (pp. 131-153). Elsevier. https://doi.org/10.1016/B978-0-443-22145-3.00006-2

Sappa, A. (2025). Adaptive machine learning models for effort estimation and risk detection in distributed software project pipelines. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 16*(2), 54–74. https://doi.org/10.58346/JOWUA.2025.I2.004

Chakrobarty, A., Sultan, T., & Cetinkaya, C. (2025). Machine learning-driven ultrasonic monitoring for quality assurance in additive manufacturing employing 2D phononic coupons. *Journal of Manufacturing Processes*, *141*, 416-430. https://doi.org/10.1016/j.jmapro.2025.02.083

Fernandes, Z., & Malhotra, S. (2023). Automation of the Operation of Machines in Construction Industries. *International Academic Journal of Innovative Research, 10*(2), 65–70. https://doi.org/10.71086/IAJIR/V10I2/IAJIR1015

Zhang, J., Yin, C., Farbiz, F., Jafary-Zadeh, M., & Sing, S. L. (2025). Advancing machine learning applications for in-situ monitoring and control in laser-based metal additive manufacturing: a state-of-the-art review. *Virtual and Physical Prototyping*, *20*(1), e2592732. https://doi.org/10.1080/17452759.2025.2592732

Purnama, D. A., Alfiqra, A., & Cahyo, W. N. (2025). A machine learning-driven Six Sigma framework for enhancing the quality improvement and productivity in the Aircraft Manufacturing. *OPSI*, *18*(1), 136-151. https://doi.org/10.31315/opsi.v18i1.13960

Vempati, S., Rao, S., Srinivasulu, Haritha, Kocharla, S., & Kannadhasan, S. (2025, January). Intelligent Additive Manufacturing is Unleashing the Power of 3D Printing with Machine Learning. In *Proceedings of Eighth International Conference on Information System Design and Intelligent Applications* (pp. 435-454). Singapore: Springer Nature Singapore. https://doi.org/10.1007/978-981-95-0375-9_33

Malashin, I., Martysyuk, D., Tynchenko, V., Gantimurov, A., Nelyub, V., & Borodulin, A. (2025). Data-driven optimization of discontinuous and continuous fiber composite processes using machine learning: a review. *Polymers*, *17*(18), 2557. https://doi.org/10.3390/polym17182557

Xiao, S., Li, J., Wang, Z., Chen, Y., & Tofighi, S. (2024). Advancing additive manufacturing through machine learning techniques: A state-of-the-art review. *Future Internet*, *16*(11), 419. https://doi.org/10.3390/fi16110419

Zohuri, B. (2024). Artificial intelligence and machine learning driven adaptive control applications. *Journal of Material Sciences and Engineering Technology*, *2*(4), 1-4.

Mo, Y., Su, J., Li, Q., Jiang, F., & Sing, S. L. (2025). Machine learning-driven design of support structures and process parameters in additive manufacturing. *Virtual and Physical Prototyping*, *20*(1), e2525988. https://doi.org/10.1080/17452759.2025.2525988

Yang, Z., Tong, X., Wang, H., Song, Z., Fu, R., & Bao, J. (2025). Digital Twin Incorporating Deep Learning and MBSE for Adaptive Manufacturing of Aerospace Parts. *Processes*, *13*(5), 1376. https://doi.org/10.3390/pr13051376

Yu, K., Yao, Y., Zhang, W., Lu, L., Gao, Q., Zhang, P., & Sing, S. L. (2025). Defects, monitoring, and AI-enabled control in soft material additive manufacturing: a review. *Virtual and Physical Prototyping*, *20*(1), e2588456. https://doi.org/10.1080/17452759.2025.2588456

He, W., Zhu, L., Liu, C., & Jiang, H. (2025). Metal additive manufacturing and molten pool dynamic characterization monitoring: Advances in machine learning for directed energy deposition. *Metals*, *15*(2), 106. https://doi.org/10.3390/met15020106

Bai, J., Wu, D., Shelley, T., Schubel, P., Twine, D., Russell, J., ... & Zhang, J. (2025). A comprehensive survey on machine learning driven material defect detection. *ACM Computing Surveys*, *57*(11), 1-36. https://doi.org/10.1145/3730576

Xames, M. D., Torsha, F. K., & Sarwar, F. (2023). A systematic literature review on recent trends of machine learning applications in additive manufacturing. *Journal of Intelligent Manufacturing*, *34*(6), 2529-2555. https://doi.org/10.1007/s10845-022-01957-6

Chandramowliswaran, A., Kumar, J., & Prasad, K. (2023). Application of machine learning based classification algorithms in additive manufacturing-A review. *Advancements In Aeromechanical Materials for Manufacturing: Icaamm-2021*, *2492*(1), 040003. https://doi.org/10.1063/5.0113275

Altun, F., Bayar, A., Hamzat, A. K., Asmatulu, R., Ali, Z., & Asmatulu, E. (2025). AI-driven innovations in 3D printing: Optimization, automation, and intelligent control. *Journal of Manufacturing and Materials Processing*, *9*(10), 329. https://doi.org/10.3390/jmmp9100329