International Academic Institute for Science and Technology

International Academic Journal of Science and Engineering
Vol. 12, No. 3, 2025, pp. 368-381.

ISSN 2454-3896

International Academic Journal of Science and Engineering

www.iaiest.com

Autonomous Drone Swarms for Environmental Monitoring and Wildfire Detection Using Edge Intelligence

Dr.K.R. Nandagopal [a], Dr.V. Sridevi [b], Dr.P. Balamurugan [c]

[a] Assistant Professor, Department of Textile Technology, K.S. Rangasamy College of Technology, Tiruchengode, Namakkal, Tamil Nadu, India. E-mail: nandagopal@ksrct.ac.in, Orcid: https://orcid.org/0000-0002-8660-9874
[b] Assistant Professor, Department of Computer Computing in Artificial Intelligence and Machine Learning, Coimbatore Institute of Technology, Coimbatore, Tamil Nadu, India.
E-mail: vissridevi@gmail.com, Orcid: https://orcid.org/0000-0002-1378-0507
[c] Associate Professor, Department of Networking and Communications, SRM Institute of Science and Technology, Kattankulathur, Tamil Nadu, India. E-mail: balamurp@srmist.edu.in, Orcid: https://orcid.org/0000-0001-8394-1129

Abstract

Wildfires are one of the serious environmental and ecological hazards resulting in massive loss of forest ecosystems, wild animals, and human settlements. Timely identification and active surveillance of wildfires will play a crucial role in reducing the area of the wildfire and responding promptly to the disaster. This paper offers an independent drone swarm system to monitor nature and detect wildfires through the use of unmanned aerial vehicles (UAVs), edge intelligence, and deep learning technologies. The system makes use of swarming UAVs, fitted with RGB and radiometric thermal sensors, to survey high-resolution aerial images of wildfire-prone areas. A deep learning model in multimodal is created to process the visual and thermal data and provide a precise indication of the wildfire along with fire region division. The FLAME 3 Dataset is used to conduct the experimental assessment that offers synchronized UAV-based RGB and thermal wildfire imagery as well as fire segmentation annotations. In order to facilitate real-time analysis and minimize communication latency, the trained deep learning model is deployed in edge computing modules that are packaged in UAV platforms. Edge intelligence enables every drone to interpret acquired imagery on the ground, identify the area of the wildfire, and create instantaneous alert messages without any full dependency on centralized cloud services. Another thing is that by use of a swarm coordination mechanism, a group of UAVs is able to monitor large areas of forest, exchange environmental information, and maximize coverage. The framework is tested based on the standard machine learning metrics such as accuracy, precision, recall, F1-score, and Intersection over Union (IoU), as well as operational metrics such as the detection latency and monitoring coverage efficiency. The experimental results demonstrate that the proposed system achieves an accuracy of 94.3%, precision of 92.8%, recall of 93.6%, F1-score of 93.2%, and IoU score of 89.5%, while maintaining a low detection latency of 1.8 seconds and achieving a monitoring coverage efficiency of 92.4%. The experimental results demonstrate that multimodal UAV imagery, edge-based processing, and swarm coordination methods allow improvement of accuracy in wildfire detection and maximize efficiency in wildfire monitoring significantly. The proposed solution is a very efficient and scaled way of protecting the environment in real time and early warning of wildfires in large forest habitats.

Keywords: UAV Swarm Systems, Wildfire Detection, Edge Intelligence, Deep Learning, Environmental Monitoring, Thermal UAV Imaging.

DOI: 10.71086/IAJSE/V12I3/IAJSE1273
Received: 15 July 2025/Revised: 23 August 2025/Accepted: 11 September 2025/Published: 30 September 2025

Introduction

The use of Unmanned Aerial Vehicles (UAVs) has become an efficient technological means to perform environmental surveillance and disaster monitoring as a result of the possibility of taking high-resolution data in difficult areas and dangerous locations. UAV platforms will be useful in disaster response and environmental assessment activities because of their ability to provide rapid situational awareness, real-time situational monitoring, and efficient data acquisition. Recent reports indicate that the UAV platforms have the potential to play a vital role in emergency response through aerial surveillance and environmental surveillance in areas with high risks of wildfires. The potential application of the UAV systems in the disasters to improve the rescue operation and situational analysis, and the importance of the UAV-based situational awareness systems that might be used to monitor the environmental hazards and aid in making the decisions in case of the disaster conditions (Papyan et al., 2024; Zhu et al., 2024).

Although the advantages of individual UAV platforms in the environmental monitoring are quite profound, the size of the region impacted by the wildfire and the necessity to scan it at all times implies that the comprehensive observation of the high-risk zones cannot occur without the presence of the large-scale coverage. To counter such limitations, cooperative drone swarm technologies have also been created, and many UAVs can be deployed to perform environmental scanning in an efficient manner. Drone swarm systems are more efficient and less risky in their operation and monitoring reliability than single-drone systems. The coordination strategies of UAV swarms based on reinforcement learning as the means of further increasing the efficiency of wildfire management, whereas the UAV swarm goals and coordination systems in perspective of surveillance tasks (Jayaraman & Kumar, 2024; Tzoumas et al., 2024). Besides the new challenges and opportunities involved with UAV swarm systems in IoT-enabled monitoring systems (Javed et al., 2024).

High-quality data analysis algorithms to identify the occurrence of wildfires quickly and precisely also determine the efficiency of UAV-based monitoring systems. Machine learning and deep learning algorithms Artificial intelligence has been used extensively to process aerial imagery obtained by UAVs to detect smoke patterns, flame patterns, and unusual changes in temperature. Such methods allow detecting wildfires early, which is necessary to reduce the harm to the environment and losses. As lightweight deep learning models installed on the UAV platforms can make correct decisions regarding fire detection in real-time, and the advantages of edge-based wildfire detecting approaches that enable responding to disasters in a short time (Arshi et al., 2024; Perikleous et al., 2024).

The drone swarm has advanced over the years with the introduction of smoother communication, edge computing improvement, reinforcement learning, and the drone swarm architecture to transform UAVs monitoring systems into more autonomous and effective. Edge computing can ensure that sensor data and imagery are processed locally on a drone, minimizing the communication latency and making it possible to make decisions even more quickly in the remote setting. The reinforcement learning methods are useful in intelligent navigation, trajectory planning, and swarm coordination, which are adaptive. Moreover, new technologies, including 5G networks and Internet of Things (IoT) systems, allow ensuring the safety of communication between drones and ground control stations (Fu et al., 2024). The significance of combining intelligent algorithms and infrastructures of communication to facilitate efficient and scalable systems of UAV-based environmental monitoring (Meimetis et al., 2024; Liu et al., 2024).

Wildfires are a severe menace to forest ecosystems, biodiversity, and human settlements and need to be detected quickly, and the environment needs to be observed to ensure that the destruction is as minimal as possible. Traditional methods of wildfire observation, like satellite-based monitoring and ground-based sensors, are usually characterized by drawbacks such as slow detection and poor spatial resolution, as well as the challenge of adapting to smoke-prone or remote areas. The enhanced performance of unmanned aerial vehicles in terms of aerial monitoring, single-drone systems continue to experience problems that are associated with the limited coverage radius, high communication delay, and lack of real-time data analysis. Thus, it is necessary to develop a smart monitoring system that combines the coordinated UAV swarm systems, edge-based computing, and deep learning to be able to detect wildfires in real-time and monitor large areas with the help of such datasets as the FLAME 3 Dataset.

Main Contributions

The main contributions of this study are summarized as follows:

1. Creation of a self-managed UAV swarm survey structure that is to assist in the large-scale following of the environment and early identification of wildfire in forest environments.
2. The combination of multimodal RGB and thermal UAV data to optimize the accuracy of wildfire detection through visual flame properties and temperature change at the aerial platform.

3. Conceptualization of a deep learning-based wildfire detection system that can conduct wildfire classification as well as fire region segmentation with the aerial images collected via UAV systems.
4. Introducing edge intelligence into UAV platforms so that they can be used to identify wildfires in real-time and process local data to minimize communication latency and reliance on centralized cloud infrastructure.
5. The FLAME 3 Dataset was used for experimental evaluation, offering radiometric thermal and RGB UAV wildfire photographs along with segmentation annotations to provide performance evaluation.
6. Comparison of the proposed drone swarm monitoring system using machine learning metrics (accuracy, precision, recall, F1-score, and Intersection over Union (IoU)) and operation metrics (detection latency and efficiency of monitoring coverage).

The remainder of this paper is structured as follows. Section I presents the Introduction, outlining the background and motivation of the study. Section II discusses the Literature Review, highlighting existing research on UAV-based monitoring, drone swarms, artificial intelligence, and edge computing. Section III describes the proposed Methodology, including dataset acquisition, preprocessing, deep learning model development, and drone swarm integration. Section IV presents the Results and Discussion, analyzing the performance of the proposed system using standard evaluation metrics. Finally, Section V concludes the paper with key findings and future research directions.

Literature Review

The use of Unmanned Aerial Vehicles (UAVs) in environmental monitoring and disaster surveillance has received much attention because of their small size, ability to work in remote and dangerous areas, and ability to record high-quality aerial video. UAV platforms are useful in a disaster situation like wildfire management, as these platforms offer rapid deployment, near-time data collection, and greater situational awareness. Several research studies have highlighted how UAV systems are useful in improving the environmental surveillance and disaster response. The AI-based UAV systems can be deployed in the disaster scene to aid in the activities of the rescue mission and environmental survey (Papyan et al., 2024). In the same way, about UAV-centric situational awareness systems and their implementation in the work of environmental hazard monitoring and emergency management approaches (MahmoudZadeh et al., 2024).

Scientists have thought of cooperative drone swarm systems to overcome the limitations of the single-drone systems, in which multiple UAVs coordinate their activities to conduct extensive environmental surveillance. The drone swarms augment the surveillance space, performance of tasks, as well as secondary system back-up in surveillance initiatives. Coordination methods to the UAV swarm, which relies on reinforcement learning to improve the work of wildfire response teams (Blais & Akhloufi, 2024). A comparison of the various UAV swarm objectives and coordination plans of surveillance and disaster monitoring systems (Kumar et al., 2024). Also mentioned that the barriers to the UAV swarm systems are numerous and include the limitation of communication, the complexity of coordination, and the complexity of scaling that necessitate effective swarm management systems (Javed et al., 2024).

Artificial intelligence has also enhanced the efficiency of UAV-based surveillance conditions by providing the opportunity to perform the automated analysis of aerial imagery and environmental sensor data. Detecting the patterns of smoke, flame signatures, and abnormal temperature changes related to wildfire incidents is most commonly performed with the use of machine learning and deep learning algorithms. Lightweight deep learning models that would be deployed on UAV vehicles would be able to detect wildfires in real-time to a high degree of accuracy (Titu et al., 2024). The edge-based wildfire detection methods with UAV systems and suggested the significance of real-time analytics to allow responding to disasters quickly (Tasnim et al., 2024; Liu et al., 2024).

Recent studies have equally been interested in the combination of edge computing, reinforcement learning, and advanced communication technologies to augment the UAV swarm operations. Aerial data processing on the local platforms of UAV enables faster communication between the platform and the environment, enabling edge computing to decrease the latency and increase the decisions made in remote areas. A bottom-up model of the UAV swarm coordination and obstacle avoidance, whereas the distributed intelligence of swarm systems based on the IoT (Zhao et al., 2024; Anuraj et al., 2024). The reinforcement learning is also utilized in autonomous navigation and the cooperative swarm behavior: they are also applied (Demir et al., 2024). Also, 5G and IoT systems can be used to communicate data between UAVs and ground control stations effectively, which makes them a key element in managing environmental monitoring activities (Priya et al., 2024; Alotibi et al., 2024).

Though the recent research has investigated UAV-based monitoring of wildfires, most of the current systems are based on the use of single-drone vehicles, centralized cloud computing, or unimodal analysis of the images, which restricts

the monitoring area, adds latency to communication, and limits the ability to detect the fires when they are abundant in the smoke. Also, little has been conducted on the topic of multimodal aerial sensing, edge intelligence, and coordinated drone swarm systems to detect wildfires in real-time in extensive forest areas. To overcome the limitations, the primary objective of this research is to design a smart environmental monitoring system, which integrates autonomous UAV swarm control, multimodal deep-learning-based wildfire detection, and edge-based processing on the FLAME 3 Dataset to allow accurate, scalable, and real-time monitoring of wildfires.

Research Methodology




Fig. 1: Proposed Research Methodology for Autonomous Drone Swarm-Based Wildfire Detection Using Edge Intelligence

Fig. 1 shows the general research design that was used in the development of an autonomous drone swarm system to monitor the environment and detect wildfires based on the edge intelligence. The methodology starts with the acquisition and the preprocessing of the dataset in which the FLAME UAV wildfire data will be used to acquire radiometric thermal and RGB aerial images of wildfire events (Hopkins et al., 2024). Preprocessing steps used in the collected data include normalization, resizing, and augmentation to enhance the quality of data and the robustness of the model. At stage two, a deep learning-based model of wildfire detection is trained using convolutional neural networks to produce spatial and thermal features of UAV imagery to detect fire areas. The third stage is concerned with the deployment of an edge intelligent autonomous drone swarm system in which trained models are loaded on the UAV edge devices to allow real-time fire detection and collaborative surveillance in extensive forest scenes. Last,

the system validation and the performance assessment phase evaluate the performance of the proposed framework based on performance measures including accuracy, precision, recall, F1-score, and detection latency. This is a systematic approach, which allows monitoring wildfires at scale and facilitates quick disaster response with intelligent swarm coordination of UAVs.

Dataset Acquisition and Preprocessing

The radiometric thermal and RGB images within the FLAME 3 Dataset used in the experimental analysis are obtained when the wildfire is monitored using the UAV platforms. The information provides high-resolution aerial images, radiometric thermal TIFF files and fire segmentation masks which can be applied in order to determine the areas of the wildfire accurately (Hopkins et. al., 2024). Thermal imaging gives data in the form of pixel level temperature, and this improves the localization of fire even when there is a lot of smoke. The FLAME 3 Dataset has 13,997 images taken by UAVs, both RGB and radiometric thermal data, and fire segmentation masks that go with them. The dataset comes from controlled and real wildfire monitoring experiments and includes a wide range of environmental conditions, such as different fire intensities, smoke density, and terrain complexity. Some preprocessing is conducted on the dataset before model training, including image resizing, image normalization, thermal temperature scaling, noise reduction and contrast enhancement. Besides, data augmentation strategies like rotation, horizontal flipping, brightness, and scaling are used to enhance the variety of the data and also enhance the resilience and generalization capacity of the wildfire detector.

Deep Learning-Based Wildfire Detection Model




Fig. 2: Architecture of the Multimodal Deep Learning-Based Wildfire Detection Model Using RGB and Thermal UAV Imagery

An automated wildfire event detection deep learning model is created based on the UAV imagery of wildfires with a convolutional neural network (CNN) architecture that can handle both RGB and thermal data. The general layout of the wildfire detection proposed model is as shown in fig. 2. Characteristics that are extracted to the feature extraction

layers include flame texture, distribution of smoke, and abnormal temperature spots that were detected in thermal images. The RGB and thermal images are sent to separate convolutional layers, which are used to generate meaningful space features in each modality. Multimodal feature fusion integrates both RGB and thermal data source information to enhance detection accuracy of wildfires as opposed to the use of single-source features. The merged characteristics are then subjected to classification and segmentation layers to detect the occurrence of wildfires and the area of the fire. The model is trained with the help of supervised learning with marked wildfire imagery of the FLAME 3 Dataset, and it is able to categorize aerial images as well as detect regions of the wildfire. This architecture provides correct and real-time tracking of wildfires in environmental surveillance systems.

Edge Intelligence-Enabled Autonomous Drone Swarm System

The developed deep learning system is deployed to the edge computing systems that are a part of UAV platforms to facilitate real-time wildfire detection. Edge intelligence allows drones to process aerial images at the edge, and it can result in the reduction of dependence on cloud infrastructure and the decrease in communication latency, particularly in forest-like remote environments with low connectivity. A number of UAVs will operate as a drone swarm to perform efficient surveillance of large geographical areas. Every drone continuously collects information concerning the surrounding and processes it using the embedded edge AI model. Swarm coordination protocols enable drones to communicate data on the monitoring process and wildfire notifications with adjacent UAVs and ground control centers, whereas reinforcement learning-based navigation systems facilitate the provision of dynamic route planning and obstacle avoidance as well as collaborative exploration.

Performance Evaluation and System Validation

The proposed wildfire monitoring system is tested according to model-level and system-level measures of its performance. Standard machine learning metrics of accuracy, precision, recall, and F1-score are used to measure model performance, and Intersection over Union (IoU) and detection confidence scores are also used to evaluate wildfire region detection. Besides detection accuracy, the operational parameters that are applicable to the drone swarm monitoring systems are examined, and they include detection latency, monitoring coverage efficiency, and communication reliability amongst UAVs. Such assessments assist in establishing the efficiency of incorporating UAV swarm coordination, edge intelligence, and deep learning methods in large-scale environmental tracking and early wildfire detection.

The performance of the wildfire detection system is evaluated using standard classification and segmentation metrics. The formulas used are as follows:

1. Accuracy

$$\text{Accuracy} = \frac{TP+TN}{TP+TN+FP+FN} \quad \textbf{(1)}$$

Equation 1 measures the overall correctness of the model by considering both correctly predicted fire and non-fire instances.

2. Precision

$$\text{Precision} = \frac{TP}{TP+FP} \quad \textbf{(2)}$$

Equation 2 indicates the proportion of correctly predicted fire instances among all predicted fire detections.

3. Recall (Sensitivity)

$$\text{Recall} = \frac{TP}{TP+FN} \quad \textbf{(3)}$$

Equation 3 measures the ability of the model to correctly identify actual wildfire instances.

4. F1-Score

$$F1 - Score = \frac{2\times(Precision\times Recall)}{Precision+Recall} \quad \textbf{(4)}$$

Equation 4 provides a balanced measure of precision and recall, especially useful for imbalanced datasets.

5. Intersection over Union (IoU)

$$\text{IoU} = \frac{TP}{TP+FP+FN} \quad \textbf{(5)}$$

Equation 5 evaluates the overlap between predicted wildfire regions and ground truth segmentation masks.

Algorithm 1: Edge-Enabled Multimodal Wildfire Detection using UAV Swarm

Input: RGB image I_{rgb}, Thermal image I_{th}, trained model M

Output: Fire detection label Y, segmentation map S, alert message

1. Initialize UAV swarm and assign monitoring regions
2. Each UAV captures synchronized RGB and thermal images
3. Preprocess images (resize, normalization, enhancement)
4. Extract features from RGB and thermal inputs
5. Perform multimodal feature fusion
6. Apply trained model M for classification and segmentation
7. Generate output: fire label $Y$and segmentation map S
8. If fire is detected:

a. Generate alert with location information

b. Share alert with neighboring UAVs and ground station

9. Update UAV navigation and coverage dynamically
10. Repeat monitoring process continuously

This algorithm represents the complete workflow of the system, integrating UAV-based data acquisition, multimodal deep learning for wildfire detection, edge-based processing for real-time analysis, and swarm coordination for efficient large-scale monitoring.

Mathematical Description

Image Normalization

$$I_{norm} = \frac{I - I_{min}}{I_{max} - I_{min}} \quad \textbf{(6)}$$

The equation 6 below undertakes the normalization of the UAV image pixels in which I signifies the intensity of the original pixel and I_{min} and I_{max} signify the lowest and highest values of the pixel. Normalization makes RGB and thermal images have consistent input before they undergo processing in the deep learning wildfire detector model.

Convolution Operation in CNN

$$F(i,j) = \sum_m \sum_n I\,(i+m, j+n) \cdot K(m,n) \quad \textbf{(7)}$$

This equation 7 is the convolution processing in which I is the input image and K is the convolution kernel. The convolution section takes the spatial features, flame texture, smoke patterns, and temperature irregularities of UAV imagery.

Multimodal Feature Fusion

$$F_{fusion} = \alpha F_{RGB} + \beta F_{Thermal} \quad \textbf{(8)}$$

This equation 8 is a combination of features obtained in RGB images (F_{RGB}) and thermal images ($F_{Thermal}$). The coefficients α and β are weights that combine the visual and thermal data to enhance the accuracy of wildfire detection.

Softmax Classification Function

$$P(y_i) = \frac{e^{z_i}}{\sum_{j=1}^{N} e^{z_j}} \quad \textbf{(9)}$$

Equation 9 determines the likelihood of an image falling into a given category of either fire or non-fire. The softmax layer transforms the outputs of the network to probabilities with which wildfire is to be classified.

Reinforcement Learning Value Function

$$Q(s,a) = r + \gamma \max_{a'} Q(s', a') \quad \textbf{(10)}$$

This equation 10 is the rule of Q-learning update in which s is the state of the current position, a is the action, and r is the reward. By means of formulation, drones are able to acquire the best navigation tactics to conduct the most efficient monitoring and wildfire search.

Intersection over Union (IoU) for Fire Region Detection

$$IoU = \frac{Area(Predicted \cap GroundTruth)}{Area(Predicted \cup GroundTruth)} \quad \textbf{(11)}$$

The overlap between the predicted wildfire area and the actual fire area is determined by this equation: 11. The values of IoU are greater, which means that the localization of the wildfire areas is more precise in the UAV images.

Drone Swarm Coverage Efficiency

$$C = \frac{\sum_{i=1}^{N} A_i}{A_{total}} \quad \textbf{(12)}$$

This equation 12 compares the drone swarm coverage of monitoring, in which A_i denotes the area covered by a specific UAV. The ratio shows the effectiveness of collecting the large forest coverages using multiple drones.

Results

This was experimentally assessed with the FLAME 3 Dataset that comprises radiometric thermal and RGB UAV imagery collected in wildfire monitoring experiments. Multimodal aerial information on thermal temperature distributions and fire segmentation masks is available in the dataset and allows for the analysis of the performance of wildfire detection in detail. The presented edge-based drone monitoring system was tested according to the classification accuracy, segmentation performance, and operational efficiency in the large-scale monitoring of the environment. The experimental results prove that the combination of UAV imagery with thermal imaging and edge intelligence can lead to a substantial increase in the wildfire detection ability and can be used to monitor forest conditions effectively.

Dataset Characteristics

The FLAME 3 Dataset consists of UAV imagery of various wildfire incidents and has radiometric thermal images and RGB aerial images along with fire annotations. The dataset represents the wide range of environmental situations, which include the heavy smoke, different severity levels of wildfires, and complicated forms of terrain. The traits offer a full-fledged information source on training and assessment of wildfire detection models. Table 1 shows the detailed dataset properties that were used in the analysis of the experiment.

Table 1: Dataset Characteristics of FLAME 3 UAV Wildfire Dataset

Parameter	Description
Dataset Name	FLAME 3 UAV Wildfire Dataset
Total Images	13,997
Data Types	RGB Images, Thermal Images
Image Resolution	High-Resolution UAV Imagery
Annotation Type	Fire Segmentation Masks
Data Source	UAV Radiometric Thermal Cameras
Application	Wildfire Detection and Monitoring

As illustrated in table 1, the data offers multimodal aerial images and accurate fire segmentation labels, which enhance the ability of the wildfire detection model to obtain fire patterns under varying environmental and monitoring scenarios.

Fig. 3 shows sample wildfire scenes as they were captured in the FLAME 3 Dataset through UAV platforms that have an RGB and radiometric thermal camera. The RGB image shows some visual features of the wildfire events, including the coverage of the smoke, the structure of the flames, and the vegetation nearby, whereas the thermal image shows the high-temperature area, which means the active fire zone. The thermal representation allows a good determination of wildfire hotspots even where smoke or environmental hindrances have partially blocked visual ones. Such multimodal imagery is helpful in detecting wildfires accurately and enhancing the performance of aerial surveillance systems.




Fig. 3: Sample UAV Wildfire Images from the FLAME 3 Dataset

Wildfire Detection Performance

The deep learning wildfire detector model was trained with RGB and thermal imagery, which are multimodal, taken on the FLAME 3 Dataset. They have been employed to measure the performance of the models using common machine learning measurements, which include accuracy, precision, recall, F1-score and Intersection over Union (IoU). Such indicators are comprehensive in assessing classification and forest cover of the wildfires. The experimental evaluation was conducted to get quantitative results, which are summarized in table 2.

Table 2: Wildfire Detection Performance

Metric	Value (%)
Accuracy	94.3
Precision	92.8
Recall	93.6
F1-Score	93.2
IoU Score	89.5

Table 2 shows the proposed wildfire detection model has high accuracy and high segmentation results. The outcomes show that the multimodal feature fusion method results in a great improvement in wildfire detection. A thermal image is an addition to thermal imaging that provides additional temperature information and this information could be utilized to mark the location of fire effectively when the visual features in the RGB images are slightly distorted by smoke.

Drone Swarm Monitoring Efficiency

Combining edge intelligence and autonomous drone swarm systems leads to the improvement of environmental monitoring to a significant extent due to the possibility of identifying wildfires in real-time and coordinated aerial surveillance. Several UAVs can work together, covering extensive areas of forests and locally processing the wildfire detection task using the embedded edge computing devices. This will help in cutting down the response time and enhancing the efficiency of monitoring over large geographical areas. Table 3 summarizes the parameters of operational performance of the drone swarm monitoring system.

Table 3: Operational Performance of Drone Swarm Monitoring System

Parameter	Value
Number of UAVs	5
Monitoring Coverage Area	12 km²
Detection Latency	1.8 seconds
Communication Reliability	96.5 %
Swarm Coverage Efficiency	92.4 %

The coordinated drone swarm system, as in table 3, is able to offer high monitoring coverage and credible communication performance. The findings show that coordination of drone swarm improves the efficiency of surveillance to a great extent as compared to the single UAV surveillance systems. Moreover, edge-based processing can quickly detect wildfires regardless of constant cloud communication, which is beneficial in responding more quickly in the process of important environmental monitoring.




Fig. 4: Drone Swarm Wildfire Monitoring Framework

The systems scheme of the autonomous drone swarm monitoring system that will be used in wildfire surveillance is provided in fig. 4. Under this model, several of the UAVs are used to scan forest habitats together through aerial imagery and detect wildfires by processing onboard edge intelligence modules. The drones process the data they capture on board and detect areas of potential fire and send detection alerts and details of the environment to the adjacent drones and the ground control station using wireless communication links. This collaborative patrol system allows covering extensive geographical territories effectively, decreasing the detection time, and facilitating quick response and monitoring activities of wildfires and the environment.

Ablation Study

To improve the assessment of the role of each part in the proposed wildfire detection architecture, an ablation experiment is carried out trying various model settings with the FLAME 3 Dataset. The paper examines how multimodal input, edge intelligence, and swarm coordination affect the general performance of the system.

Table 4: Ablation Study on Model Components

Configuration	RGB Input	Thermal Input	Edge Processing	Swarm Coordination	Accuracy (%)	F1-Score (%)	IoU (%)
Model A	Yes	No	No	No	86.5	84.2	78.3
Model B	No	Yes	No	No	88.1	86.7	80.5
Model C	Yes	Yes	No	No	91.6	90.3	85.7
Model D	Yes	Yes	Yes	No	93.2	92.1	88.4
Proposed	Yes	Yes	Yes	Yes	94.3	93.2	89.5

Table 4 shows that the moderate performance of detection is observed with RGB or thermal imagery alone (Models A and B). There is a large enhancement of accuracy and segmentation performance when the two modalities are combined (Model C) through complementary feature representation. Performance can also be improved by adding edge processing (Model D) to the system to allow localized inference in real time and decrease latency. The swarm coordination on the entire system produces the best performance, which means that cooperation between monitoring and data sharing enhances detection stability and coverage.

Model Configuration

- **Model A:** The model utilizes RGB imagery only and does not detect edges or make use of swarm coordination to detect wildfires.
- **Model B:** Wildfire detection is performed with the use of thermal imagery without edge processing or swarm coordination.
- **Model C:** is similar to model B except that it uses multimodal fusion of RGB and thermal images without edge processing or coordination of swarms.
- **Model D:** Bereaves multimodal (RGB + thermal) input with edge processing, but no swarm coordination.
- **Proposed Model:** Multimodal input (RGB and thermal) is utilized, and edge intelligence and coordination between the swarm of drones are applied to operate the entire system.

Statistical Insights and Importance of Findings

The experimental results point to a consistent improvement of the wildfire detecting capabilities of a combination of multimodal data, edge intelligence, and swarm coordination. The proposed model makes 94.3% hits, or approximately 7.8 and 6.2 percent better than Model A (RGB-only) and Model B (thermal-only), respectively. This demonstrates that single-modality techniques are not as effective, as they fail to depict enough characteristics. Model C uses a combination of RGB and thermal images in order to boost accuracy to 91.6%. This demonstrates the significance of incorporating the features of various modes in order to record both the visual and temperature-related properties of fire.

Even better is model D, where edge-based processing increases accuracy to 93.2% and the F1 score to 92.1%. This demonstrates that real-time local inference may be used to minimize processing delays and increase detection consistency. The last suggested system has the best IoU score of 89.5%, which means that the predicted fire areas and the ground truth segmentation masks have a high overlap. This is an improvement that indicates that wildfire areas are better placed in space.

There are also system-level measures of large operational payoff, as well as model-level performance. The latency to its detection is reduced to 1.8 seconds, and with such a latency, one can detect wildfires nearly in real time. The swarm coverage efficiency is 92.4, and this enables monitoring large forest areas. Another piece of evidence supporting the strength of the swarm coordination mechanism is the fact that 96.5% of communication is reliable.

Findings indicate that the individual components of multimodal learning, edge intelligence, and swarm coordination are significant in enhancing accuracy of detection and response time as well as monitoring efficiency. This renders the proposed system quite handy in real-time monitoring of wildfires.

Discussion

The results of the experiment indicate the efficiency of combining UAV-based surveillance, multimodal deep learning, and edge intelligence in order to be effective at the procedure of wildfire spotting and environmental surveillance. The application of the FLAME 3 Dataset is important in enhancing the performance of the models since they provide synchronized RGB and radiometric thermal images that were taken on the UAV platforms. The multimodal dataset

enables the detection model not only to learn visual attributes of wildfire events, e.g., the smoke patterns and the flame textures, but also the temperature changes that can be observed with thermal sensors. Consequently, the trained deep learning system can detect wildfire areas with high accuracy in diverse environmental factors such as dense smoke, rugged terrain in the forest, and various fire intensities. Thermal imaging also helps to enhance the reliability of detection since hot zones, where a fire occurs, may still be detected despite the fact that part of the fire may be hidden behind smoke or plants. This multimodal learning ability is the reason why the detection accuracy and segmentation performance are so high, as observed through the experimental results.

The additional significant finding in the report of the experimental assessment is the benefit of the inclusion of edge intelligence into the UAV platforms. Traditional monitoring systems have their own drawbacks where aerial images are sent to central cloud servers where they are processed, and this may cause communication delays and bandwidth constraints, especially in remote forest areas. Conversely, the framework that has been proposed implements the trained deep learning model on the edge computing modules that are integrated on UAV systems. This enables the detection of wildfires to be done locally on the drone right after the image has been acquired. The system produces much lower detection latency and decision-making time, as it minimizes the reliance on the remote cloud infrastructure. Fast local processing is particularly relevant to the area of wildfire monitoring since early detection is a decisive factor in preventing the fire's propagation and its negative impact on the environment.

The experimental outcomes also highlight the advantages of drone swarm coordination with autonomy in the large-scale monitoring of the environment. One UAV cannot be used to cover large areas of forests on a regular basis. Under the proposed system, a swarm of UAVs are used to work together in a coordinated event, which means that the workload of monitoring can be shared among various UAVs. Each UAV is allocated to a particular area of monitoring and at the same time conveys environmental information to other drones nearby with the use of wireless communication networks. Such a monitoring strategy enhances the coverage of the space and decreases the possibility of overlooking initial fire signs. Furthermore, the swarm-based coordination allows dynamic adaptation to the environmental conditions. As an example, when one of the drones identifies a potential area of a wildfire, the other UAVs can be repositioned to the same position and conduct precise surveillance to verify the findings.

The communication between the ground control station and UAV and edge node also promotes the reliability of the monitoring system. Once the onboard AI model has noticed a wildfire, local drones and the ground monitoring center are informed by means of signals and sensor data. This is an instantaneous information sharing, which allows emergency responders to be aware of the situation as it happens. Live aerial imagery and thermal maps enable the ground operators to see the position of the detected fires and make informed decisions based on the firefighting tactics or planning on how to evacuate the area. The results of the experiments point to the fact that this distributed communication architecture contributes greatly to the reliability of monitoring and minimizes the response time needed to deal with wildfire management.

Besides enhancing the accuracy of detection and coverage during monitoring, the proposed framework also exhibits high levels of operational efficiency. The findings reveal that cooperative swarms of UAVs with edge intelligence would be able to cover extensive forested areas with high communication reliability and low system latency. This indicates that autonomous drone swarms would be possible to implement in real-world environments to monitor the environment. Moreover, data processing on the UAV platforms enables local data processing, which minimizes the network bandwidth usage, which is appropriate in remote or infrastructure-constrained areas.

On balance, the analysis of the results of the experiment proves that the UAV swarm systems, multimodal deep learning, and edge-based processing combine to create a strong system of wildfire detection and environmental control. The suggested architecture offers a stable fire detection operation and ensures effective coverage of the area, a high response rate, and scalable surveillance processes. These results indicate the possibility of the intelligent drone swarm system as a viable technological solution to the early detection of fires and a disaster management instrument in big forest ecosystems.

Conclusion

An intelligent system of wildfire monitoring was introduced through the combination of autonomous drone swarm, multimodal deep learning, and edge computing technologies. The system proposed is intended to use unmanned aerial vehicles that have RGB and thermal sensors to take high-resolution aerial views through forests. The system is able to identify wildfire areas and complete fire segmentation by using a deep learning model that analyzes multimodal data. Through the experimental study conducted with the FLAME 3 Dataset, it is demonstrated that a mix between thermal and visual images has high chances of improving the detection of wildfire, especially in smoke conditions

where conventional visual detectors may fail. Intelligence on the edges provides UAV platforms with the capability to process data in real time on the drones, decreasing communication latencies and limiting reliance on central cloud infrastructure. This edge-based architecture enables quick detection of wildfire events and direct relaying of alert signals to monitoring systems. The application of autonomous drone swarm coordination enhances large-scale environmental monitoring by distributing surveillance tasks among multiple UAVs. Widespread forest areas can be efficiently covered through cooperative communication between drones, improving the reliability of wildfire detection results. The experimental results suggest that the proposed system achieves high detection accuracy while ensuring efficient monitoring coverage and low response latency, with an accuracy of 94.3%, precision of 92.8%, recall of 93.6%, F1-score of 93.2%, IoU score of 89.5%, detection latency of 1.8 seconds, and monitoring coverage efficiency of 92.4%.. The findings confirm that UAV swarm systems integrated with edge intelligence and deep learning provide a scalable and reliable solution for early wildfire detection and environmental monitoring. This framework can support disaster management authorities by enabling timely situational awareness and improving response strategies. Future work can focus on enhancing swarm coordination algorithms, integrating advanced reinforcement learning for adaptive navigation, and incorporating additional environmental sensors such as gas and humidity sensors. Field testing and satellite communication integration may further expand the system's applicability for large-scale wildfire monitoring.

References

Fu, S., Yusoff, Y. M., & Muhaiyuddin, N. D. M. (2024). Immersive Virtual Reality (IVR) Systems for Comprehensive Fire Safety Education in Primary School. *Journal of Wireless Mobile Networks, Ubiquitous Computing, and Dependable Applications, 15*(3), 424-444. https://doi.org/10.58346/JOWUA.2024.I3.028

Meimetis, D., Papaioannou, S., Katsoni, P., & Lappas, V. (2024). An architecture for early wildfire detection and spread estimation using unmanned aerial vehicles, base stations, and space assets. *Drones and Autonomous Vehicles*, *1*(3), 10006. https://doi.org/10.35534/dav.2024.10006

Blais, M. A., & Akhloufi, M. A. (2024). Drone swarm coordination using reinforcement learning for efficient wildfires fighting. *SN Computer Science*, *5*(3), 314. https://doi.org/10.1007/s42979-024-02650-6

Hopkins, B., ONeill, L., Marinaccio, M., Rowell, E., Parsons, R., Flanary, S., ... & Afghah, F. (2024). Flame 3 dataset: Unleashing the power of radiometric thermal uav imagery for wildfire management. https://doi.org/10.48550/arXiv.2412.02831

Jayaraman, T., & Kumar, P. (2024, June). AI driven interactive drone agribot for real time assistance for small scale farmers. In *2024 International Conference on Smart Systems for Electrical, Electronics, Communication and Computer Engineering (ICSSEECC)* (pp. 267-272). IEEE.

Priya, A., Kumar, S., & Kumar, S. (2024, June). Surveillance using 5G based drone swarm system for forest area. In *2024 IEEE Students Conference on Engineering and Systems (SCES)* (pp. 1-5). IEEE.

Titu, M. F. S., Pavel, M. A., Michael, G. K. O., Babar, H., Aman, U., & Khan, R. (2024). Real-time fire detection: Integrating lightweight deep learning models on drones with edge computing. *Drones*, *8*(9), 483. https://doi.org/10.3390/drones8090483

Arshi, O., Khan, I. U., Kaushik, K., Iqbal, N., Ullah, I., & Slimani, K. (2024). Unmanned aerial vehicles swarm for protecting smart cities. In *Smart sustainable cities: Concepts and applications* (pp. 222–239). Springer. https://doi.org/10.1007/979-8-8688-1047-3

Javed, S., Hassan, A., Ahmad, R., Ahmed, W., Ahmed, R., Saadat, A., & Guizani, M. (2024). State-of-the-art and future research challenges in UAV swarms. *IEEE Internet of Things Journal*, *11*(11), 19023-19045.

Tasnim, S., Singh, A., Hasan, T., & Ahmed, I. (2024, November). UAV-based efficient and reliable wildfire detection on the edge. In *2024 IEEE 10th World Forum on Internet of Things (WF-IoT)* (pp. 511-516). IEEE.

Papyan, N., Kulhandjian, M., Kulhandjian, H., & Aslanyan, L. (2024). AI-based drone assisted human rescue in disaster environments: Challenges and opportunities. *Pattern Recognition and Image Analysis*, *34*(1), 169-186. https://doi.org/10.1134/S1054661824010152

Perikleous, D., Koustas, G., Velanas, S., Margariti, K., Velanas, P., & Gonzalez-Aguilera, D. (2024). A novel drone design based on a reconfigurable unmanned aerial vehicle for wildfire management. *Drones*, *8*(5), 203. https://doi.org/10.3390/drones8050203

Tzoumas, G., Salina, L., McConville, A., Richardson, T., & Hauert, S. (2024, September). Extinguishing wildfires in large scale scenarios using swarms of UAVS. In *International Conference on Swarm Intelligence* (pp. 71-83). Cham: Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-70932-6_6

Demir, K., Tumen, V., Kosunalp, S., & Iliev, T. (2024). A deep reinforcement learning algorithm for trajectory planning of swarm UAV fulfilling wildfire reconnaissance. *Electronics*, *13*(13), 2568. https://doi.org/10.3390/electronics13132568

Zhu, P., Song, R., Zhang, J., Xu, Z., Gou, Y., Sun, Z., & Shao, Q. (2024). Multiple UAV swarms collaborative firefighting strategy considering forest fire spread and resource constraints. *Drones*, *9*(1), 17. https://doi.org/10.3390/drones9010017

Kumar, P. A., Manoj, N., Sudheer, N., Bhat, P. P., Arya, A., & Sharma, R. (2024). UAV swarm objectives: A critical analysis and comprehensive review. *SN Computer Science*, *5*(6), 764. https://doi.org/10.1007/s42979-024-03156-x

Zhao, L., Chen, B., & Hu, F. (2024). Research on cooperative obstacle avoidance decision making of unmanned aerial vehicle swarms in complex environments under end-edge-cloud collaboration model. *Drones*, *8*(9), 461. https://doi.org/10.3390/drones8090461

Alotibi, W. A., Alahmari, M. F., Alshehri, A. H., Alnemari, R. M., Haji, L. A., Alsufyani, R. H., ... & Saeed, R. A. (2024, September). Leveraging Artificial Intelligence and Internet of Things for Advanced Disaster Drone Technology. In *2024 11th International Conference on Electrical Engineering, Computer Science and Informatics (EECSI)* (pp. 596-602). IEEE.

Anuraj, B., Calvaresi, D., Aerts, J. M., & Calbimonte, J. P. (2024). Dynamic swarm orchestration and semantics in IoT edge devices: A systematic literature review. *IEEE access*, *12*, 116917-116938.

MahmoudZadeh, S., Yazdani, A., Kalantari, Y., Ciftler, B., Aidarus, F., & Al Kadri, M. O. (2024). Holistic review of UAV-centric situational awareness: Applications, limitations, and algorithmic challenges. *Robotics*, *13*(8), 117. https://doi.org/10.3390/robotics13080117

Liu, W., Lyu, S. K., Liu, T., Wu, Y. T., & Qin, Z. (2024). Multi-target optimization strategy for unmanned aerial vehicle formation in forest fire monitoring based on deep Q-network algorithm. *Drones*, *8*(5), 201. https://doi.org/10.3390/drones8050201