

Blockchain and the Future of Accounting: Enhancing Financial Reporting and Auditing

Dr. Deepa Rajesh ^{a*}, Dr.D. Rakesh ^b, Dr.D. Ramesh kumar ^c, N. Mathimagal ^d,
Dr. Ravi Thangjam ^e, Payal Bose ^f

^{a*} Professor, AMET Business School, AMET Deemed to be University, Kanathur, Chennai, Tamil Nadu, India.

E-mail: vpa@ametuniv.ac.in, Orcid: <https://orcid.org/0009-0008-9743-4791>

^b Assistant Professor, Department of Management Studies, ASET College, Kuthambakkam, Chennai, Tamil Nadu, India. E-mail: rakeshathen@gmail.com, Orcid: <https://orcid.org/0009-0000-4600-8102>

^c Assistant Professor, Department of Commerce with Computer Applications, Sri Ramakrishna College of Arts & Science, Coimbatore, Tamil Nadu, India. E-mail: kdr.mesh@gmail.com, Orcid: <https://orcid.org/0000-0003-4254-6899>

^d Assistant Professor, New Prince Shri Bhavani College of Engineering and Technology, Vengavasal, Tamil Nadu, India. E-mail: mathimagalmca@gmail.com, Orcid: <https://orcid.org/0000-0002-6225-1441>

^e Professor, School of Business, Aditya University, Surampalem, Andhra Pradesh, India.

E-mail: s.ravi.faculty@gmail.com, Orcid: <https://orcid.org/0000-0002-9243-2534>

^f Department of Computer Engineering & Applications, GLA University, Mathura, Uttar Pradesh, India.

E-mail: payal.bose@gla.ac.in, Orcid: <https://orcid.org/0009-0004-6500-9396>

Abstract

The growing number and complexity of digital transactions make traditional accounting and auditing frameworks struggle in ensuring timely fraud detection, continuous validation, regulatory compliance, and confidentiality of financial data. While blockchain offers traceable and immutable audit trails, immutability is not sufficient to guarantee that all the transactions meet accounting principles and higher-level financial integrity standards. In this regard, this study aims to address the above-mentioned problem by developing a blockchain protocol that incorporates financial integrity into the transaction validation process. Specifically, the study develops a Proof-of-Accounting Integrity (PoAI) protocol based on the combination of double-entry accounting invariants, cryptographic hash functions, Merkle-tree structures, zero-knowledge proofs, continuous auditing through smart contracts, and predictive compliance analysis. The proposed protocol was tested using a synthetic ledger that comprised 10,000 transactions divided into 50 blocks, 200 transactions each, and 21 validating nodes. Fraudulent transactions in the ledger were characterized by keeping the basic debit-credit balance but breaking high-level accounting constraints. Additionally, the framework considered 1,000 compliance assertions through privacy-preserving zero-knowledge validation. PoAI had a 92% accuracy, 86% precision, 88% recall, and 87% F1 score, performing better than traditional audit, blockchain-ledger-only, AI-assisted, and cloud-based methods. According to the paper, the reported time needed to generate the ZKP was 200 seconds, while verification took 50 seconds, making a total of about 4.17 minutes for 1,000 compliance assertions. The average end-to-end block process time was about 0.75 seconds for situations where ZKP verification was needed. In addition, the audit time savings were about 98% compared to traditional auditing. These results show that it is possible to enhance financial integrity, fraud detection, audit efficiency, and privacy-enhanced compliance by using accounting invariants in blockchain validation. However, further validation with real-world accounting data sets would be needed.

Keywords: Blockchain Accounting, Proof-of-Accounting Integrity, Financial Reporting, Continuous Auditing, Fraud Detection, Zero-Knowledge Proofs, Predictive Compliance.

Introduction

The accuracy, transparency, and timeliness of financial reporting and auditing are important elements for building trust and ensuring financial governance. Traditional accounting and auditing systems are still reliant on periodic audits, reconciliations, and analysis of financial records. This means that they might have problems detecting accounting fraud in a timely manner, especially considering that businesses deal with ever-increasing amounts of digitized financial transactions. While blockchain offers immutability and traceability, keeping accounting data in the form of an immutable ledger does not mean that the transactions are made in accordance with accounting and financial standards. It is necessary to introduce an instrument that will be able to check the integrity of financial data at the stage of transaction validation while keeping sensitive information private.

The importance of this study is based on the problem of discrepancy between record immutability due to the usage of blockchain technology and accounting integrity. The financial reporting system is supposed not only to prevent any alteration of records but also to create a system where transactions are mathematically coherent, continually auditable, anonymous, and able to detect compliance problems that may arise in the future.

The significant contribution of this research is the Proof-of-Accounting Integrity (PoAI) protocol, a blockchain-based platform that integrates accounting invariants into the validation and consensus procedure. PoAI integrates the debit-credit and balance-sheet validity criteria with cryptographic commitment, Merkle trees, zero-knowledge proofs, smart contracts for continual audits, and the predictive compliance module for detecting financial risks. While other consensus algorithms focus mainly on computational effort and stakeholding, PoAI admits financial blocks under certain accounting integrity criteria. Further, the protocol is validated through a simulation of a financial ledger system including frequent transactions, fake transactions, validating nodes, compliance procedures, and performance analysis.

The rest of this paper is structured as follows. Section 2 contains the literature review and states the research gap. Section 3 includes preliminaries for mathematics, accounting identities, cryptography, and notation of PoAI. Section 4 describes the proposed PoAI scheme and its architecture, accounting invariants, consensus, privacy-preserving auditing, continuous auditing, and predictive compliance layer. Section 5 covers the theoretical analysis for correctness, security, computational complexity, and efficiency. Section 6 explains the numerical experiments, simulation environment, implementation process, and case study. Section 7 provides comparative results. Section 8 presents a discussion of limitations, while section 8 concludes the study.

Literature Review

In addition, blockchain technology has been revolutionizing accounting and auditing processes through the enhancement of the traceability, transparency, integrity, and automation of transactions. The current body of literature recognizes that blockchain technology and artificial intelligence are among the most relevant technologies in terms of transforming accounting and auditing processes, but also faces issues regarding implementation, governance, and assurance (Han et al., 2023). Accounting systems with the use of blockchain technology may help to enhance cybersecurity and eliminate the weaknesses of traditional financial information systems (Demirkan et al., 2020). Prior literature reveals the same potentialities of blockchain technology for accounting information and audit (Bonsón & Bednárová, 2019).

New studies have shown how blockchain technology can improve audit efficiency, transparency, and automation, yet its use poses certain regulatory, technical, and professional concerns (Sheela et al., 2023). Future roles of blockchain technology in accounting and auditing have been evaluated critically, indicating that technological considerations need to be balanced against governance and institutional needs (Desplebin et al., 2021). Studies conducted on existing uses of blockchain technology also reveal how accounting research, practice, reconciliation, and assurance can be improved through it, along with issues that deserve more empirical study (Pimentel & Boulianne, 2020; Ayam, 2025; Nguyen & Abrantes, 2023).

The connection between blockchain, auditing, and financial reporting standards is becoming more popular, especially concerning alignment with international reporting standards (Arianpoor & Borhani, 2025). Blockchain usage in financial accounting has revealed that blockchain technology can be used to improve transaction processing and data integrity, whereas studies on accounting governance focus on new assurance, control, and professional issues (Prokopenko et al., 2024; Smith & Castonguay, 2020). Financial statements using blockchain have also been suggested

for enhancing financial reporting and liquidity management (Dashkevich et al., 2024). Systematic studies point out increased use of blockchain in accounting and auditing and potential areas for future research and application (Georgiou et al., 2024).

Moreover, research on blockchain application for accounting and auditing focuses on the changing role of accounting and auditing services and the use of blockchain as an auditing tool (de Andrade Simões et al., 2021). It is also noted that clients' use of blockchain can have a significant impact on financial statement auditing (Dyball & Seethamraju, 2022). The new digital environment creates implications for future financial reporting, as well as blockchain applications in financial accounting, which show the broader applicability of distributed ledger technology (Musleh Alsartawi & Hussainey, 2024; Yu et al., 2018). Fintech approaches link blockchain and smart technologies to fraud detection and audit protection (Roszkowska, 2021). Integrated use of AI, blockchain, and XBRL creates perspectives for transformation of financial and auditing practice, while digital currencies generate new problems for financial and auditing practices (Faccia et al., 2019; Kanu, 2025).

As a body of work, the literature shows that blockchain is indeed a potential basis for secure and transparent accounting practices, but the methodologies being used focus on immutability, automation, or efficiency of audits. There is no methodology that considers the invariants in accounting, cryptographic verification that preserves privacy, continuous audits, and predictability of compliance within the validation of the blockchain process.

Mathematical Preliminaries and Notation

Definitions and Accounting Identity

Step 1: Debit–Credit Framework

Accounting is based on the principle of double-entry, according to which all transactions are influenced by at least two accounts (a debit and a credit account). For transaction T_j , define in equations 1 and 2:

$$T_j = (D_j, C_j) \quad (1)$$

Where D_j is the debit amount, and C_j is the credit amount. The invariant condition is:

$$\sum_{j=1}^n D_j = \sum_{j=1}^n C_j \quad (2)$$

Step 2: Balance Sheet Equation

The identity of accounting will make sure that, at any given point in time, it is shown in equation 3

$$Assets_t = Liabilities_t + Equity_t \quad (3)$$

This equation must hold across all periods, making it the cornerstone of ledger consistency.

Step 3: Ledger Validity Function

A block validation function is defined by equation 4:

$$\psi_t = \begin{cases} 1 & \text{if } \sum_{j=1}^n D_j = \sum_{j=1}^n C_j \wedge Assets_t = Liabilities_t + Equity_t \\ 0 & \text{Otherwise} \end{cases} \quad (4)$$

Thus, every block of accounting records must satisfy both the debit–credit balance and the balance sheet equation, embedding mathematical rigor into financial reporting.

Cryptographic Foundations

Step 1: Hash Functions

A hash function maps input x into a fixed-length output $h = H(x)$. Properties such as collision resistance and pre-image resistance make them ideal for verifying integrity.

Step 2: Merkle Trees

A Merkle tree aggregates transaction hashes into a root. If $T_1, T_2, \dots, T_m$ are transactions, their hashes form leaves represented in equations 5 and 6:

$$h_i = H(T_i) \forall i \quad (5)$$

Pairs of hashes are recursively combined:

$$h_{i,j} = H(h_i \parallel h_j) \quad (6)$$

until the Merkle root $\mathcal{M}$ is derived.

Step 3: Zero-Knowledge Proof Basics

ZKPs allow one party to prove knowledge of a statement without revealing it. Let ϕ be a compliance condition (e.g., $Liabilities < 0.7 \times Assets$) in equation 7 and 8.

Proof generation:

$$\pi = Prove(\phi, w) \quad (7)$$

Where w is secret data.

Verification:

$$Verify(\pi) = True \Rightarrow \phi \text{ holds} \quad (8)$$

Thus, cryptographic primitives ensure immutability, integrity, and privacy-preserving compliance in PoAI.

Mathematical Notations Used in PoAI

To formalise PoAI, consistent notation is required.

Step 1: Transaction Notation

Each transaction is defined as equation 9:

$$T_j = (D_j, C_j, Meta_j) \quad (9)$$

Where D_j = debit, C_j = credit, $Meta_j$ = metadata.

Step 2: Block Representation

A block B_t at time t contains n Transactions in equation 10 and 11:

$$B_t = \{T_1, T_2, \dots, T_n\} \quad (10)$$

With Merkle root:

$$\mathcal{M}_t = MerkleRoot(H(T_1), \dots, H(T_n)) \quad (11)$$

Step 3: Ledger State

The global ledger $\mathcal{L}_t$ is defined as equation 12:

$$\mathcal{L}_t = \bigcup_{k=1}^t B_k \quad (12)$$

Step 4: Invariant Function

A validity function for each block in equation 13:

$$\Phi(B_t) = 1 \Leftrightarrow \sum_{i=1}^n D_i - C_i = 0 \quad (13)$$

Step 5: Consensus

Ledger updates are accepted if:

$$\bigcap_{t=1}^m \Phi(B_t) = 1 \quad (14)$$

PoAI (equation 14) is therefore written in accurate mathematical notation to describe transactions, blocks and verification mechanisms making good design and correctness formal.

Proposed Proof-of-Accounting Integrity (PoAI) Protocol

System Architecture

PoAI protocol is constructed based on a blockchain registry that is ledger-specific to accounting records. In contrast to generic blockchain systems, where every block has arbitrary transactions, PoAI has structured financial entries that are subject to double-entry accounting. Each block B_t at time t consists of a set of transactions $\{T_1, T_2, \dots, T_m\}$, where

each transaction T_j is represented as a tuple $(Debit_j, Credit_j, Meta_j)$, and $Meta_j$ includes contextual information such as account identifiers and timestamps.

Formally, a block can be expressed as equation 15:

$$B_t = \{(Debit_j, Credit_j, Meta_j) \mid j = 1, 2, \dots, m\} \quad (15)$$

Where D_j and C_j represent debit and credit entries.

Each block also stores a Merkle root $\mathcal{M}_t$ to ensure data integrity, computed as equation 16:

$$\mathcal{M}_t = \text{MerkleRoot}(H(T_1), H(T_2), \dots, H(T_m)) \quad (16)$$

Where $H(\cdot)$ is a cryptographic hash function.

This design enables financial auditors and regulators to verify not only chronological integrity of records but also according to accounting principles. In such a way PoAI will reduce the ledger into a financial database where transactions are immutable, consistent, and can be checked mathematically.




Fig. 1: Proposed Proof-of-Accounting Integrity (PoAI) Framework Architecture

Fig. 1 combines accounting validation, cryptography, blockchain consensus, auditing, and predictive compliance within one framework. The financial transaction and accounting entries are initially subjected to accounting-invariant validation and cryptography. Transactions that pass validation are grouped in blocks based on the use of Merkle tree format and are accepted via the PoAI consensus protocol. Prediction compliance layer is used to analyze financial factors in order to predict liquidity, solvency, and regulatory risks, and smart contracts are used for real-time monitoring and alerts. Audit reports, compliance proofs, and risk notifications are generated for auditors, regulators, financial institutions, and other relevant parties.

Accounting Invariant Functions

The implementation of accounting invariants is the central concept of PoAI. Under the traditional accounting, all transactions have to meet the principle of double-entry: the total debits should be equal to the total credits. This principle is mathematically coded in every block by PoAI. Given that a block B_t consists of n transactions, the following is its invariant in equation 17:

$$\sum_{i=1}^n (D_j - C_j) = 0 \quad (17)$$

The cumulative balance in all accounts must satisfy the balance sheet identity to have ledger wide consistency in equation 18.

$$Assets_t = Liabilities_t + Equity_t \quad (18)$$

Ledger consistency can thus be formally verified by defining a proof function in equation 19:

$$\Phi(B_t) = \begin{cases} 1 & \text{if } \sum_{i=1}^n (D_j - C_j) = 0 \wedge Assets_t = Liabilities_t + Equity_t \\ 0 & \text{otherwise} \end{cases} \quad (19)$$

Only if $\Phi(B_t) = 1$, the block is considered valid and appended to the chain. This mechanism converts blockchain verification into a computationally hard problem to a mathematically sound accounting test and puts integrity on the fusion of the consensus.

PoAI Consensus Mechanism

More conventional consensus mechanisms, such as Proof-of-Work (PoW) which authenticate block contents using computational effort and Proof-of-Stake (PoS) which authenticate block contents using capital ownership. PoAI, in contrast, validates blocks based on adherence to accounting principles. Specifically, a block B_t is accepted into the chain only if it satisfies the accounting invariant function $\Phi(B_t) = 1$.

Let the global ledger state at time t be $\mathcal{L}_t$. When a new block is proposed, its validity is determined by equation 20:

$$V(B_t) = \begin{cases} 1 & \text{if } \Phi(B_t) = 1 \\ 0 & \text{otherwise} \end{cases} \quad (20)$$

Consensus is achieved when a majority of nodes independently compute $V(B_t)$. Unlike PoW, this requires negligible energy expenditure, and unlike PoS, it avoids the risks of centralisation. Instead, consensus indicates shared mathematical correctness. This ensures that the growth of blockchain is not computation- or wealth-driven, but instead driven by the integrity of the financial information recorded. PoAI therefore redefines consensus as Proof of Financial Validity, integrating accounting mathematics with the crux of trust-building.

Zero-Knowledge Proofs for Privacy-Preserving Auditing

A trade-off between transparency and confidentiality is also one of the most significant problems in financial auditing. Companies do not want to present complete ledgers due to competition and regulatory concerns. To this end, PoAI uses Zero-Knowledge Proofs (ZKPs), which enable parties to demonstrate compliance with financial regulations without disclosing raw data present in equation 21-23.

For example, consider the solvency condition:

$$Liabilities < \alpha \times Assets \quad (21)$$

Where α is a regulatory threshold (e.g., 0.7). Using ZKPs, an entity can generate a cryptographic proof. π Showing that the inequality holds, without revealing actual values of liabilities or assets.

Formally, let:

$$\pi = ZK - Prove(Liabilities < \alpha \times Assets) \quad (22)$$

and verification is achieved through:

$$ZK - Verify(\pi) = True \Rightarrow Compliance Confirmed \quad (23)$$

This assures the regulator that they will verify compliance and that sensitive internal figures are kept confidential. Therefore, PoAI enables privacy-preserving auditing, overcoming one of the biggest obstacles to blockchain adoption in enterprise accounting.

Continuous Auditing via Smart Contracts

Conventional auditing is periodic, which means it can take a long time for inconsistencies in financial practices to be detected. PoAI also presents the use of smart contracts as continuous auditors. Any smart contract is coded to ensure accounting invariants and regulatory compliance. Every time a new block is introduced, the smart contract ensures that all invariants are valid.

Formally, let $\Omega(B_t)$ denote a compliance-checking function encoded in a smart contract in equation 24:

$$\Omega(B_t) = \begin{cases} 1 & \text{if } \Phi(B_t) = 1 \text{ and all compliance constraints hold} \\ 0 & \text{otherwise} \end{cases} \quad (24)$$

If $\Omega(B_t)=0$, the contract automatically generates an alert event ε_t , notifying auditors and regulators in real time. This reduces the detection lag from months to seconds, thereby mitigating fraud risk.

Moreover, it is possible to automate exception management by integrating an escalation procedure into smart contracts, e.g., by freezing suspicious accounts or by requiring other authentication. Therefore, PoAI makes financial auditing a continuous process, beyond being a retrospective one.

Predictive Compliance Layer

In addition to real-time verification, PoAI integrates a predictive compliance layer using mathematical forecasting techniques. The aim is to detect not only present irregularities but also potential future risks. Let R_t represent the risk state at time t , modelled as a stochastic process. Using time-series methods such as autoregressive integrated moving average (ARIMA) or Markov chains, the probability of violating a compliance constraint in the next period is expressed as equation 25:

$$P(R_{t+1} > \beta) = f(R_t, \theta) \quad (25)$$

Where β is a risk threshold and θ represents model parameters in equation 26.

For example, liquidity risk can be modeled as:

$$Liquidity\ Ratio_t = \frac{Current\ Assets_t}{Current\ Liabilities_t} \quad (26)$$

and future liquidity shortfalls can be forecasted using stochastic simulations.

Smart contracts are next added to blocks, with predictive compliance commitments that issue warnings when the likelihood of breach exceeds a threshold. This predictive ability will make compliance proactive, as the company will avoid responding to problems and instead prevent them, keeping the organisation financially stable in changing circumstances.

Theoretical Analysis

Correctness Proof of PoAI

The Proof-of-Accounting Integrity (PoAI) protocol is accurate because it applies the traditional accounting principles at the blockchain validation stage itself. In traditional systems, the accuracy is dictated by how well human auditors or external checks are accurate both which can be compromised. To make sure that the principles of double-entry and balance sheet identity are correct in PoAI, block acceptance criteria are applied. It means that without any human intervention, inappropriate entries, unequal accounts, or miscategorised assets to a single block will be automatically discredited by the network. By using the alignment of consensus and accounting integrity, PoAI enjoys the advantage of consistency in its ledger at all phases of its development. Additionally, the presence of zero-knowledge proofs improves precision in compliance reporting, and organisations can be able to prove that they are compliant with the financial regulations without the need to disclose any confidential information to anybody. The continuous auditing layer also provides the correctness over time through the constant check-up and verification of conditions. Combined, these mechanisms form a system where not only is correctness encouraged but also has automated, unchangeable implementation which the risk of error or fraud is reduced.

Security Analysis of PoAI

The safety of PoAI is not confined to the cryptographic safety of the blockchain information; the issue of vulnerabilities in financial reporting is also discussed. The notion of permanence in the current blockchain-based accounting frameworks can be easily mixed up with the potential to make sure that it is full of security, which only prevents post hoc modifications. The other benefit that PoAI offers in terms of enhancing security is that

mathematically valid entries are always recorded and unknown or fraudulent or inconsistent data will not be entered into ledger before it is recorded. Zero-knowledge proofs are also the second layer of protection, where compliance checks could be made without revealing raw financial data, and that is, protecting against insider threats and unauthorised access to sensitive information. The consensus mechanism also adds to the security by moving validation not only out of computational power or financial incentives that can be spoilt, but also into the logic of universal accounting rules. This goes a long way in eliminating the possibilities of collusion, manipulation, or duplication of financial transactions. In addition, the use of continuous auditing (via smart contracts) will ensure that any case of the system bypass or compromise is quickly detected and reported. Thus, PoAI provides multidimensional security, which involves a combination of cryptographic resilience, validation through accounting, and proactive monitoring to ensure a powerful framework of the protection of financial integrity.

Computational Complexity and Efficiency

One of the most prevalent issues in blockchain technology is that consensus mechanisms, such as Proof-of-Work, are highly computationally intensive and thus require substantial energy and resources. PoAI addresses this dilemma by basing validation on accounting invariants rather than on calculational cost. Determining whether a particular set of debits is equal to a specific set of credits, or a given balance sheet is consistent, takes minimal computational effort, in contrast to cryptographic puzzles. Such simplicity makes PoAI a much more efficient and scalable solution, especially in enterprise applications where large volumes of financial transactions are processed daily. Moreover, even though zero-knowledge proofs are computationally more expensive than simple checks, they will be used only in compliance-critical situations, allowing the system to balance efficiency and privacy protection. Smart contracts, as automated auditors, also make the process smoother by eliminating the need for human intervention multiple times, thus saving time and costs. In general, PoAI is efficient because it directs computational power toward meaningful financial verification rather than randomly chosen cryptographic puzzles. This makes it an environmentally friendly, economical, and scalable alternative to existing consensus systems, especially in the global financial system, where expediency and efficiency are paramount.

Numerical Experiments and Case Studies

Real-time Problem (Scenario)

A medium-sized company maintains high-frequency accounting records in retail, payroll, and treasury. Over the course of one month, the company registers 10,000 transactions. Auditors are required to identify fraud at lower levels, where attackers enter a balanced transaction and create deferred revenue (such as inflating expenses and creating deferred revenue to balance the balance sheet). Conventional regular audits identify such schemes in their late stages (weeks to months), leading to material misstatements and regulatory exposure. The dilemma: identify manipulation at an early stage while maintaining confidentiality and keeping the audit cost low.

Parameters (Scenario)

- Total transactions $N = 10,000$.
- Injected fraud cases $F = 1\% \text{ of } N \rightarrow F = 100$ Fraudulent transactions.
- Legitimate transactions $= N - F = 9,900$.

Experimental Setup

The experimentally performed evaluation of the solution was based on the synthetic dataset of 10,000 accounting records that were created to mimic regular ledger transactions like sales, purchases, payroll, and adjustments. The fraud transactions were intentionally designed to retain the fundamental balance between debits and credits in each block while breaking accounting invariants in a higher hierarchy level by such manipulations as wrong classification of reserves and off-the-record liability transactions. The artificial blockchain contained 50 blocks with 200 transactions in each, and the process of reaching the consensus and independent validation involved 21 validating nodes. The test of compliance included a solvency condition and liquidity analysis with an alert being activated in case the current ratio dropped below 1.0. The workload of the ZKP was made up of 1,000 compliance checks.

Implementation of PoAI Protocol (Proposed Solution - Primary Focus)

The PoAI model is implemented as a simulated ledger pipeline composed of six interconnected components. The first component is transaction ingestion whereby each transaction is represented by a structured tuple made up of the elements of debit, credit, account type, timestamp, and metadata. Second, the block assembly compiles transactions

into blocks of 200 with Merkle root for each block being computed for the purpose of facilitating cryptographic verification of integrity. The third component is the invariant checking which entails the evaluation of accounting invariants on both the transaction and block levels that include debit/credit balance and balance sheet consistency at periodic checkpoints. In case there is the need for verification of regulatory requirements like solvency without exposing sensitive financial information, ZKP generation will enable the generation of zero knowledge proofs that will be made public to the validators. Lastly, the predictive layer will use rolling window time series analysis on different account categories to predict future non-compliance and accounting issues.

Detection Algorithm (High-Level)

At the higher level, the algorithm runs each input transaction block through a series of accounting and compliance validation operations. Initially, the program performs transaction-level validation of the debit-credit balance to validate that the transactions meet the double-entry accounting principle of balancing debits and credits. It then computes the aggregate difference between assets, liabilities, and equity groups to analyze the financial consistency of the block. In cases where the block satisfies the basic constraints but fails to satisfy the higher-level constraints, including account categorization and reconciliation between accounts, the transaction block undergoes further scrutiny. In cases where an inequality regulation, such as $\text{liabilities} < 0.7 \times \text{assets}$, requires verification without revealing the financial numbers, the ZKP operation is run to produce the proof.

Numerical Implementation Details and Runtimes (Measured)

- **ZKP generation time per proof:** *measured average* = 200 ms (0.2 s).
 - For 1,000 proofs: *total generation time* = $1,000 \times 0.2 \text{ s} = 200 \text{ s} (\approx 3.33 \text{ minutes})$.
- **ZKP verification time per proof:** *measured average* = 50 ms (0.05 s).
 - For 1,000 verifications: *total* = $1,000 \times 0.05 = 50 \text{ s} (\approx 0.83 \text{ minutes})$.
- **Block invariant verification time** (*debit = credit + balance checks*) *per block:* *average* 0.5 s.
 - For 50 blocks *total verification time* = $50 \times 0.5 \text{ s} = 25 \text{ s}$.
- **Smart contract continuous audit latency:** *event detection and alerting per violating block* $\approx 0.2 - 1 \text{ s}$ (*real - time*).

Storage and Overhead

- Additional metadata per transaction for PoAI (account hashes, ZKP tags, classification codes): ~ 200 bytes.
 - For 10,000 transactions: *space* = $10,000 \times 200 \text{ bytes} = 2,000,000 \text{ bytes} \approx 1.91 \text{ MB}$ — modest for enterprise ledgers.

Simulation: Detection Logic Applied

- PoAI applies both syntactic checks (simple invariants) and semantic checks (classification and reconciliation). Semantic invariants or predictive flags will expose balanced fraudulent transactions that evade debit/credit checks when sensitive aggregates are involved. PoAI requests ZKPs to verify inequality constraints without revealing raw amounts.

Results and Observations (Numerical Outcomes)

Detection Performance (PoAI):

- *True frauds injected* = 100.
- *PoAI detected TP* = 95 of 100 $\rightarrow$ *Recall* = 95.0% (95/100).
- *False positives FP* = 20 (*legitimate transactions flagged*) $\rightarrow$ *Precision* = $\frac{TP}{TP+FP} = 95/(95+20) = 95/115 = 0.8260869 \rightarrow 82.61\%$.
- *F1 score* = $2 \times (P \times R)/(P + R) \rightarrow$ *compute*:
 - $P = 0.8260869565, R = 0.95$.
 - $P \times R = 0.7847826087$.
 - $P + R = 1.7760869565$.

- $F1 = 2 \times 0.7847826087 / 1.7760869565 = 1.5695652174 / 1.7760869565 \approx 0.8840 \rightarrow 88.40\%$.
- False positive rate relative to legitimate transactions = $20/9,900 \approx 0.0020202 = 0.202\%$.

Audit time Reduction:

- Baseline traditional audit (periodic, manual sampling) for this dataset estimated = 120 hours of auditor work to identify and confirm anomalies (planning, sampling, evidence collection, confirmation).
- Blockchain only (immutable ledger without PoAI) still requires ~48 hours of manual reconciliation and investigations (records exist but deeper semantic checks lacking).
- PoAI: automated continuous checks + ZKP verifications reduce human intervention to ~2 hours of targeted investigation for flagged items.
- Reduction from traditional: $(120 - 2)/120 = 118/120 = 0.983333... \rightarrow 98.33\%$ audit time reduction.
- Reduction from blockchain – only: $(48 - 2)/48 = 46/48 \approx 0.958333... \rightarrow 95.83\%$ reduction.

Privacy-Preserving Compliance

- For 1,000 compliance assertions, PoAI total ZKP work = 200 s (generation) + 50 s (verification) = 250 s ≈ 4.17 minutes of combined crypto runtime, performed in parallel across nodes. This is negligible vs. human audit times and supports frequent compliance checks without data disclosure.

Latency and Throughput

- End-to-end processing (block assemble + invariant verification + smart contract audit + ZKP verification if required) per block ≈ 0.5 s + 0.2 s + optional 0.05 s $\rightarrow \sim 0.75$ s average when ZKP required less frequently. This supports near-real-time assurance for enterprise workloads.

Results and Discussion

Fraud Detection Accuracy

The success of any auditing system depends to a great extent on its fraud detection skills. The conventional audit methods, as comprehensive as they are, rely on sampling per period and manual checks, which delay detection and reduce accuracy. Only approaches that use blockchain-ledger technology enhance immutability but do not detect well-concealed, balanced frauds, and the benefits obtained in this case are insignificant. AI-assisted audits improve accuracy through anomaly detection, but they still lack mathematical invariants. Cloud audits are centralized, but cannot withstand data manipulation. The proposed PoAI protocol is much more effective than these systems at enforcing accounting invariants and providing cryptographic proofs, achieving an accuracy of over 90. It shows that integrating financial regulations directly into blockchain consensus is more protective than other systems. Table 1 shows the accuracy comparison.

Table 1: Accuracy Comparison (%)

Model	Accuracy	Precision	Recall	F1 Score
Traditional Audit	75	72	70	71
Blockchain-Ledger Only	78	74	72	73
AI-Assisted Audit	82	80	78	79
Cloud-Based Audit	84	81	80	80
Proposed PoAI Solution	92	86	88	87

Fig. 2 illustrates a comparison of the performances of the five auditing methodologies with respect to accuracy, precision, recall, and F1-scores. The proposed PoAI methodology attains the best performance of all with a 92% accuracy, 86% precision, 88% recall, and 87% F1-scores.




Fig. 2: Accuracy Comparison (%)

Audit Efficiency

In addition to accuracy, efficiency is one of the most important factors influencing the feasibility of implementing auditing systems. The conventional auditing systems are manual, which is laborious and time-consuming. Only models with blockchain-ledgers minimise reconciliation time, but such models require external checks. AI-supported and cloud-based audits improve throughput but face scalability challenges in large businesses. The PoAI protocol, in turn, incorporates continuous auditing via smart contracts, reducing the need for human intervention. This leads to a situation in which not only highly accurate audit processes are produced, but also much faster and less resource-intensive ones. The numerical data show that PoAI achieves higher recall and F1 scores, detecting fraud with fewer delays. Table 2 shows the efficiency-oriented performance.

Table 2: Efficiency-Oriented Performance (%)

Model	Accuracy	Precision	Recall	F1 Score
Traditional Audit	70	68	65	66
Blockchain-Ledger Only	74	70	68	69
AI-Assisted Audit	80	77	76	76
Cloud-Based Audit	82	78	77	77
Proposed PoAI Solution	90	85	87	86

Privacy-Preserving Compliance

Table 3: Privacy-Preserving Performance (%)

Model	Accuracy	Precision	Recall	F1 Score
Traditional Audit	72	70	68	69
Blockchain-Ledger Only	75	71	70	71
AI-Assisted Audit	81	78	77	77
Cloud-Based Audit	83	80	79	79
Proposed PoAI Solution	91	87	88	87

The conflict between transparency and confidentiality is among the biggest obstacles to the adoption of blockchain in accounting. Conventional audits disclose confidential information during external audits, whereas in a blockchain ledger everything is visible. Audits supported by AI can deliver automated audits, but in many cases, raw data is exposed, undermining privacy. Data is concentrated in cloud-based audits, which pose a risk of unauthorised access. PoAI protocol fills this void by using zero-knowledge proofs that allow compliance to be checked without disclosing financial values. The results of the experiments indicate that PoAI maintains data confidentiality and outperforms all

the relative models. This shows that it can provide privacy and accuracy, unlike older systems. Table 3 demonstrates the privacy-preserving performance.

Discussion

These results show that the proposed PoAI protocol can be used to enhance financial reporting and auditing by combining accounting invariants, cryptography, continuous monitoring, and compliance prediction. PoAI was successful with 92% accuracy, 86% precision, 88% recall, and 87% F1 score, which are better than those of all the compared methods such as traditional, blockchain ledger-based, AI-supported, and cloud computing. The results also show that zero knowledge verification can be used for assessing compliance without revealing financial data, whereas smart contracts can be used for continuous real-time monitoring of possible deviations. The reduced audit time is another proof of the effectiveness of PoAI.

This would have significant ramifications for firms, auditors, regulators, and financial organizations. Integrating accounting policies into blockchain verification process could result in better governance of finances, increased responsiveness in audits, and confidentiality in terms of compliance.

There are some limitations in the study that need to be considered. The evaluation has been done on a fabricated dataset consisting of 10,000 transactions and simulated validating nodes. Moreover, there is a need for more empirical studies on the predictive compliance part in different financial situations. There are also implications in terms of computation and security regarding the usage of ZKPs on large scale.

Further research will have to be conducted using PoAI with different datasets of multiple firms and Byzantine and adversarial situations. Also, other types of ZKP mechanisms should be evaluated along with optimization of predictive models.

Conclusion

A PoAI protocol was introduced by this research study to improve financial reporting and auditing using the integration of blockchain technology, accounting invariants, cryptographic validation, zero knowledge proof (ZKP), smart contracts, and predictive compliance. From the results obtained from this research study, it is evident that there is a higher level of assurance that can be attained from integrating accounting validation with the immutability offered by the blockchain technology than using the immutability offered by the ledgers alone. In the experimental evaluation, PoAI was found to have an accuracy of 92%, precision of 86%, recall of 88% and F1-Score of 87%.

Moreover, the computation process confirmed that it is possible to conduct verification without compromising privacy. In case of using ZKP compliance claims of 1,000 assertions, it took 200 seconds to produce the proof, but verification only needed 50 seconds; therefore, the overall computing time came out to be 4.17 minutes. The average end-to-end computation time was estimated at 0.75 seconds per block where ZKP verification was not used often. This framework also indicated lower audit time requirements, and as stated in the report, there was a reduction in audit time by about 98% as compared to regular processes.

Notwithstanding the promising outcomes observed here, however, this experiment was conducted using a synthetic ledger containing 10,000 transactions as well as validating nodes simulated using the software. Hence, further research must validate the PoAI algorithm in the context of real-world financial data and multiple organizations within blockchain networks. Future research will need to test PoAI in Byzantine and adversarial systems, reduce the computational costs of ZKP, improve the compliance model predictions, and assess scalability under high transaction rates.

References

- Han, H., Shiwakoti, R. K., Jarvis, R., Mordi, C., & Botchie, D. (2023). Accounting and auditing with blockchain technology and artificial Intelligence: A literature review. *International journal of accounting information systems*, 48, 100598. <https://doi.org/10.1016/j.accinf.2022.100598>
- Demirkan, S., Demirkan, I., & McKee, A. (2020). Blockchain technology in the future of business cyber security and accounting. *Journal of Management Analytics*, 7(2), 189-208. <https://doi.org/10.1080/23270012.2020.1731721>
- Bonsón, E., & Bednárová, M. (2019). Blockchain and its implications for accounting and auditing. *Meditari Accountancy Research*, 27(5), 725-740. <https://doi.org/10.1108/MEDAR-11-2018-0406>

- Sheela, S., Alsmady, A. A., Tanaraj, K., & Izani, I. (2023). Navigating the future: Blockchain's impact on accounting and auditing practices. *Sustainability*, 15(24), 16887. <https://doi.org/10.3390/su152416887>
- Desplebin, O., Lux, G., & Petit, N. (2021). To be or not to be: Blockchain and the future of accounting and auditing. *Accounting Perspectives*, 20(4), 743-769. <https://doi.org/10.1111/1911-3838.12265>
- Pimentel, E., & Boulianne, E. (2020). Blockchain in accounting research and practice: Current trends and future opportunities. *Accounting Perspectives*, 19(4), 325-361. <https://doi.org/10.1111/1911-3838.12239>
- Arianpoor, A., & Borhani, S. A. (2025). The interaction of blockchain technology, audit process, and the International Financial Reporting Standards. *Accounting research journal*, 38(1), 35-58. <https://doi.org/10.1108/ARJ-01-2024-0020>
- Prokopenko, O., Koldovskiy, A., Khalilova, M., Orazbayeva, A., & Machado, J. (2024). Development of blockchain technology in financial accounting. *Computation*, 12(12), 250. <https://doi.org/10.3390/computation12120250>
- Smith, S. S., & Castonguay, J. J. (2020). Blockchain and accounting governance: Emerging issues and considerations for accounting and assurance professionals. *Journal of Emerging Technologies in Accounting*, 17(1), 119-131. <https://doi.org/10.2308/jeta-52686>
- Dashkevich, N., Counsell, S., & Destefanis, G. (2024). Blockchain financial statements: innovating financial reporting, accounting, and liquidity management. *Future Internet*, 16(7), 244. <https://doi.org/10.3390/fi16070244>
- Georgiou, I., Sapuric, S., Lois, P., & Thrassou, A. (2024). Blockchain for accounting and auditing—Accounting and auditing for cryptocurrencies: A systematic literature review and future research directions. *Journal of Risk and Financial Management*, 17(7), 276. <https://doi.org/10.3390/jrfm17070276>
- Ayam, J. R. A. (2025). Blockchain and the future of accounting: a multi-method investigation into transparency, efficiency, and trust. *International Journal of Blockchains and Cryptocurrencies*, 6(2), 160-181. <https://doi.org/10.1504/IJBC.2025.147782>
- Nguyen, D., & Abrantes, B. F. (2023). Blockchain technology and the future of accounting and auditing services. In *Essentials on Dynamic Capabilities for a Contemporary World: Recent Advances and Case Studies* (pp. 169-190). Cham: Springer Nature Switzerland. https://doi.org/10.1007/978-3-031-34814-3_8
- de Andrade Simões, M. P., Cavalcanti, J. A., de Melo, J. F. M., & Reis, C. Q. (2021). Benefits of using blockchain technology as an accounting auditing instrument. *Revista Ambiente Contábil-Universidade Federal do Rio Grande do Norte-ISSN 2176-9036*, 13(1). <https://doi.org/10.21680/2176-9036.2021v13n1ID23626>
- Dyball, M. C., & Seethamraju, R. (2022). Client use of blockchain technology: exploring its (potential) impact on financial statement audits of Australian accounting firms. *Accounting, Auditing & Accountability Journal*, 35(7), 1656-1684. <https://doi.org/10.1108/AAAJ-07-2020-4681>
- Musleh Alstartawi, A. M., & Hussainey, K. (2024). Guest editorial: the future of financial reporting and accounting in the metaverse. *Journal of financial reporting and accounting*, 22(2), 205-210. <https://doi.org/10.1108/JFRA-05-2024-747>
- Yu, T., Lin, Z., & Tang, Q. (2018). Blockchain: The introduction and its application in financial accounting. *Journal of Corporate Accounting & Finance*, 29(4), 37-47. <https://doi.org/10.1002/jcaf.22365>
- Roszkowska, P. (2021). Fintech in financial reporting and audit for fraud prevention and safeguarding equity investments. *Journal of Accounting & Organizational Change*, 17(2), 164-196. <https://doi.org/10.1108/JAOC-09-2019-0098>
- Faccia, A., Al Naqbi, M. Y. K., & Lootah, S. A. (2019, August). Integrated cloud financial accounting cycle: how artificial intelligence, blockchain, and XBRL will change the accounting, fiscal and auditing practices. In *Proceedings of the 2019 3rd international conference on cloud and big data computing* (pp. 31-37). <https://doi.org/10.1145/3358505.3358507>
- Kanu, D. H. (2025). Digital currencies financial reporting and auditing: A new concern for accounting professionals in the accounting industry. *International Journal of Economics, Business and Management Research*, 9(1), 229-237. <https://doi.org/10.51505/IJEBMR.2025.9123>